View NSN Online: https://aerobasegroup.kr/nsn/4210-00-889-2221

BUCKEYE FIRE EQUIPMENT CO -- PURPLE K DRY CHEMICAL -- 4210-00-889-2221

Product ID: PURPLE K DRY CHEMICAL MSDS Date:12/01/1990 FSC:4210 NIIN:00-889-2221 MSDS Number: BQMHB === Responsible Party === Company Name: BUCKEYE FIRE EQUIPMENT CO Address:102 INDUSTRIAL DR **City:KINGS MOUNTAIN** State:NC ZIP:28086 Country:US Info Phone Num:704-739-7415 Emergency Phone Num:704-73 9-7415 CAGE:57658 === Contractor Identification === Company Name: BUCKEYE FIRE EQUIPMENT CO Address:110 KINGS RD Box:428 **City:KINGS MOUNTAIN** State:NC ZIP:28086 Country:US Phone:704-739-7415 CAGE:57658 Ingred Name: MICA - SILICATES (< 1% CRYSTALLINE SILICA) CAS:12001-26-2 RTECS #:VV8760000 Other REC Limits:NONE RECOMMENDED **OSHA PEL:20 MPPCF** ACGIH TLV:3 MG/M3 RDUST; 9293 Ingred Name: POTASSIUM BICARBONATE CAS:298-14-6 Other REC L

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES AND SKIN-IRRITATES SLIGHTLY. BREATHING-IRRITATES THE RESPIRATORY SYSTEM TREAT AS MINERAL DUST. SWALLOWING-SWALLOWING LARGE QUANTITIES CAN LEAD TO ALKALOSIS. Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure: RESPIRATORY PROBLEMS-SKIN AND EYE IRRITANT. Medical Cond Aggravated by Exposure:NONE KNOWN. First Aid: FLUSH EYES WITH WATER 15 MINUTES. WASH SKIN WITH SOAP AND WATER. REMOVE TO FRESH AIR IF INHALED. RINSE MOUTH AND DRINK LARGE AMOUNTS OF WATER IF INGESTED. SEEK MEDICAL ATTENTION. _____ Flash Point:NONE Extinguishing Media:NONE. MATERIAL IS AN EXTINGUISHING AGENT. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE Spill Release Procedures: CONTAIN SPILL AND SWEEP UP. Handling and Storage Precautions: PRODUCT SHOULD BE STORED IN A CLOSED MOISTURE-FREE CONTAINER, IN A COOL, DRY LOCATION. AVOID UNNECESSARY DUST. Other Precautions: PRODUCT CANNOT BE MIXED WITH OTHER EXTINGUISHING AGENTS. Respiratory Protection: DUST RESPIRATOR REQUIRED WHEN TLV IS EXCEEDED. NUISANCE DUST (TOYTAL) 15 MG/M3. DUST RESPIRATOR RECOMMENDED WHENEVER AIRBORNE DUST IS PRESENT. Ventilation:LOCAL EXHAUST AND MECHANICAL(GENERAL) VENTILATION ARE RECOMMENDED. Protective Gloves:YES. Eye Protection:SAFETY GLASSES. Other Protective Equipment:NON

E REQUIRED. Work Hygienic Practices:USE GOOD HYGIENE AND GOOD HOUSEKEEPING PRACTICES.

Supplemental Safety and Health NONE.

HCC:N1 Melt/Freeze Pt:M.P/F.P Text:DECOMPOSES Spec Gravity:0.88 Solubility in Water:WATER REPELLANT COAT Appearance and Odor:PURPLE POWDER WITH NO CHARACTERISTIC ODOR.

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MAN UFACTURER. Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.