

DAP INC -- EPOXICAL 606 PATCHING ADHESIVE RESIN -- 8010-01-058-9510

=====
Product Identification
=====

Product ID:EPOXICAL 606 PATCHING ADHESIVE RESIN

MSDS Date:10/21/1988

FSC:8010

NIIN:01-058-9510

MSDS Number: BQMJW

=== Responsible Party ===

Company Name:DAP INC

Box:277

City:DAYTON

State:OH

ZIP:45401-0277

Country:US

Info Phone Num:800-543-3840/OHIO 513-667-4461

Emergency Phone Num:800-543-3840/O

HIO 513-667-4461

CAGE:90300

=== Contractor Identification ===

Company Name:DAP INC.

Box:277

City:DAYTON

State:OH

ZIP:45401-0277

Country:US

Phone:513-253-7154/800-543-3840

CAGE:90300

=====
Composition/Information on Ingredients
=====

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER RESIN

CAS:25068-38-6

Fraction by Wt: 60-80%

Other REC Limits:NONE SPECIFIED

Ingred Name:1,4-BUTANEDIOLDIGLYCIDYL ETHER

CAS:2425-79-8

RTECS #:EJ5100000

Fraction by Wt: 5-15%

Other REC Limits:NONE SPECIFIED

==== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:MAY IRRITATE EYES, SKIN AND
RESPIRATORY TRACT
Effects of Overexposure:MAY CAUSE SENSITIZATION. MAY CAUSE DEFATTING OF
THE SKIN LEADING TO DERMATITIS
Medical Cond Aggravated by Exposure:ALLERGY, ECZEMA OR SKIN CONDITIONS

==== First Aid Measures =====

First Aid:EYE: FLUSH WITH LARGE AMOUNTS OF
WATER FOR 15 MINUTES.
CONTACT A PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER.
INHALATION: REMOVE TO FRESH AIR. CONTACT PHYSICIAN IMMEDIATELY.
INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN OR REGIONAL
POISON CONTROL CENTER IMMEDIATELY.

==== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:>450F,>232C
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING
G SELF-
CONTAINED BREATHING APPARATUS. IS RECOMMENDED TO PROTECT FROM
COMBUSTION PRODUCTS. COOL EXPOSED SURFACES WITH WATER
Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE IF EXPOSED TO
EXTREME HEAT. ELIMINATE SOURCES OF IGNITION: ELECTRICAL EQUIPMENT,
SPARKS AND FLAME.

==== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL OR SCRAPE UP DRIED
MATERIAL AND PLACE INTO CONTAINERS.

==== Handling and Storage =====

Handling and Storage Precautions:KEEP CNTNRS TIGHTLY CLOSED WHEN NOT IN
USE AND FROM EXCESSIVE HEAT/FREEZING. VENT STORAGE AREA. KEEP AWAY
FROM CHILDREN. DO NOT STORE AT TEMP >450F.
Other Precautions:STORE AWAY FROM OXIDIZERS.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/OSHA APPROVED RESPIRATORY PROTECTION
REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL.
Ventilation:GOOD MECHANICAL V

ENTILATION AND EXHAUST.

Protective Gloves:IMPERVIOUS

Eye Protection:FULL FACE SHIELD

Other Protective Equipment:PROVIDE EYEWASH AND IMPERVIOUS APRON IF BODY CONTACT WITH PRODUCT MAY OCCUR. BARRIER CREAMS MAY BE USED.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T6

Solubility in Water:SLIGHT

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:EXCESSIVE HEAT AND FREEZING

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL STANDARDS. DO NOT REUSE EMPTY CONTAINERS. DISCARDED MATERIAL SHOULD BE INCINERATED IN A PERMITTED FACILITY. LIQUIDS CANNOT BE DISPOSED OF IN A LANDFILL .

Disclaimer (provi

ded with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.