

ARMSTRONG MACHINE WORKS -- UNKNOWN -- 5330-00-042-1033

===== Product Identification =====

MSDS Date:04/28/1993

FSC:5330

NIIN:00-042-1033

MSDS Number: BQMYB

=== Responsible Party ===

Company Name:ARMSTRONG MACHINE WORKS

Address:816 MAPLE

City:THREE RIVERS

State:MI

ZIP:49093-2345

Country:US

Info Phone Num:616-273-1415

Emergency Phone Num:616-273-1415

Preparer's Name:DGSC-SSH

CAGE:03933

=== Contracto

r Identification ===

Company Name:ARMSTRONG MACHINE WORKS

Address:816 MAPLE

Box:City:THREE RIVERS

State:MI

ZIP:49093-2345

Country:US

Phone:616-273-1415

CAGE:03933

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS (FRIABLE) (SARA III)

RTECS #:CI6425000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 - 2 FIBERS/CC

ACGIH TLV:0.2 - 2 FIBERS/CC

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingest

ion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:NOT HAZARDOUS WHEN USED AS

MANUFACTURED. EXPOSURE MAY OCCUR IF DUST IS GENERATED DUE TO ABRASIVE ACTION. ACUTE: METAL DUSTS CAN IRRITATE EYES AND UPPER RESPIRATORY SYSTEM. CHRONIC: DUST FROM ABRASIVE ACTIONS CONTAIN ASBESTOS FIBERS. OVEREXPOSURE MAY LEAD TO ASBESTOSIS AND MESOTHELIOMA. HIGHER RISK TO SMOKERS.

Explanation of Carcinogenicity:CONTAINS ASBESTOS WHICH IS LISTED BY NTP

AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:IF EXPOSED TO DUST GENERATED DUE TO ABRASIVE ACTION. INHALATION: COUGHING, WHEEZING, SHORTNESS OF BREATH, IMPAIRED PULMONARY FUNCTION. SKIN: ITCHING, RASH. EYES: MECHANICAL IRRITATION FROM AIRBORNE DUST. INGESTION: GASTROINTESTINAL DISTURBANCES.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING SKIN OR RESPIRATORY CONDITIONS MAY BE MORE AT RISK FROM EXPOSURE TO DUSTS OF THIS PRODUCT.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE. SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. EYES: FLOOD WITH WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. INGESTION: DRINK WATER. DO NOT INDUCE VOMITING. SEE DOCTOR. OTHER: CHANGE CLOTHING AS REQUIRED TO AVOID CARRYING DUST PARTICLES INTO OTHER AREAS.

===== Fire Fighting Measures =====

Flash Point:

NONE

Extinguishing Media:MATERIAL IS NOT FLAMMABLE. USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING CHEMICAL PRODUCTS.

Unusual Fire/Explosion Hazard:NONE KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. VACUUM OR WET CLEAN IF DUST IS INVOLVED. ANY VACUUM

SYSTEM SHOULD BE EQUIPPED
WITH AN OUTLET "HEPA" FILTER TO PREVENT REINTRODUCING ASBESTOS
FIBERS TO THE ATMOSPHERE.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE IN A MANNER TO MINIMIZE
FORMATION OR RETENTION OF AIRBORNE DUST. USE PROPER PERSONAL
PROTECTION FOR TASK AT HAND. CHECK W/YOUR SAFETY OFFICE!!!
Other Precautions:AS MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT
A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO ABRASIVE ACTIONS &
DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED AND BECOME
AIRBORNE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURES EXCEED ESTABLISHED LIMITS, A NIOSH/
MSHA APPROVED RESPIRATOR FOR ASBESTOS SHOULD BE USED. CONSULT YOUR
SAFETY OFFICE/INDUSTRIAL HYGIENIST PERSONNEL FOR GUIDANCE FOR THE
TASK AT HAND.
Ventilation:LOCAL EXHAUST IS RECOMMENDED IN SITUATIONS
WHERE DUST IS
GENERATED BY ABRASIVE ACTIONS, ABRASION OR OTHER MEANS.
Protective Gloves:AS REQUIRED FOR TASK AT HAND.
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES
Other Protective Equipment:AS REQUIRED FOR TASK AT HAND, AND THE
GUIDANCE SET FORTH BY YOUR SAFETY OFFICE OR INDUSTRIAL HYGIENIST
PERSONNEL.
Work Hygienic Practices:DO NOT INHALE DUST CREATED BY ABRADING ACTIONS.
USE FULL PROTECTION AGAINST AIRBORNE FIBERS.AVOID AIRBORNE DUST
CREATION
Supplemental Safety
and Health
GENERIC "MSDS" CREATED FOR "NSN" IDENTIFIED BY "DCSC" AS CONTAINING
ASBESTOS. WHEN A MANUFACTURER'S SPECIFIC "MSDS" IS PROVIDED FOR
MATERIAL PROCURED UNDER THIS NSN, THIS GENERIC "MSDS" WILL BE
REMOVED.

===== Physical/Chemical Properties =====

HCC:T6
Evaporation Rate & Reference:NONE
Solubility in Water:NOT SOLUBLE
Appearance and Odor:GASKET
Percent Volatiles by Volume:NONE

===== Stability and Reactivity Data =====

====

Stability Indicator/Materials to Avoid: YES
NONE KNOWN
Stability Condition to Avoid: NONE KNOWN

===== Disposal Considerations =====

Waste Disposal Methods: DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS. USE LANDFILLS APPROVED FOR ASBESTOS DISPOSAL. NOTE IF ITEM UNDER CONSIDERATION FOR DISPOSAL IS "FRIABLE OR NON-FRIABLE".

Disclaimer (provided with this information by the compiling agencies)

:
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.