

FARSTAD OIL INC. -- GASOLINE, UNLEADED (ALL GRADES) -- 9130-01-272-0983

=====
Product Identification
=====

Product ID:GASOLINE, UNLEADED (ALL GRADES)

MSDS Date:07/01/1990

FSC:9130

NIIN:01-272-0983

MSDS Number: BQNJQ

=== Responsible Party ===

Company Name:FARSTAD OIL INC.

Box:1842

City:MINOT

State:ND

ZIP:58702

Country:US

Info Phone Num:701-852-1194

Emergency Phone Num:701-852-1194

CAGE:JO755

=== C

Contractor Identification ===

Company Name:FARSTAD OIL INC

Address:COUNTY RD 19 N

Box:1842

City:MINOT

State:ND

ZIP:58701

Country:US

CAGE:3R470

Company Name:FARSTAD OIL INC.

Address:COUNTY RD 19N

Box:1842

City:MINOT

State:ND

ZIP:58702

Country:US

Phone:701-852-1194

CAGE:JO755

=====
Composition/Information on Ingredients
=====

Ingred Name:GASOLINE - PRODUCT MIXTURE CONTAINING THE FOLLOWING
HAZARDOUS INGREDIENTS.

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: 100%

Other REC L

imits:NONE RECOMMENDED
OSHA PEL:300 PPM/500 STEL
ACGIH TLV:300 PPM/500STEL;9293

Ingred Name:BENZENE (SARA III)
CAS:71-43-2
RTECS #:CY1400000
Fraction by Wt: 0.1-4.9%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9293
EPA Rpt Qty:1000 LBS
DO
T Rpt Qty:1000 LBS

Ingred Name:CUMENE (SARA III)
CAS:98-82-8
RTECS #:GR8575000
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)
CAS:95-63-6
RTECS #:DC3325000
Fraction by Wt: 5G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:INHALATION: MODERATE RISK OF VAP

OR

INTOXICATION. MAJOR RISK IS ENCLOSED SPACES WITH POOR VENTILATION.
SKIN: DEFATTING WITH DRYING AND CRACKING CAN LEAD TO DERMATITIS AND
SECONDARY INFECTION. EYE: IRRITANT. INGESTION: BURNING OF MOUTH
AND UPPER GI TRACT, VOMITING AND DIARRHEA. PROLONGED OR REPEATED
CONTACT: DERMATITIS.

Explanation of Carcinogenicity:CONTAINS B [71-43-2] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALATION MAY CAUSE EUPHORIA, LUNG IRRITATION

AND EDEMA, HEADACHE, DIZZINESS, DROWSINESS, CONVULSIONS, COMA,
CYANOSIS, GENERALIZED DEPRESSION. INGESTION MAY CAUSE GENERAL
DEPRESSION, SEDATION, RESPIRATORY DEPRESSION, COMA.

Medical Cond Aggravated by Exposure:MAY AGGRAVATE PRE-EXISTING

DERMATITIS, RESPIRATORY ILLNESS, OR OTHER CONDITIONS WHICH HAVE THE
SAME SYMPTOMS OR EFFECTS AS STATED ABOVE.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING

EYELIDS OPEN. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH
SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. FOR RESPIRATORY
DISTRESS, GIVE AIR, OXYGEN, OR CPR IF NECESSARY. INGESTION: DO NOT
INDUCE VOMITING. KEEP HEAD BELOW HIPS IF VOMITING OCCURS TO PREVENT
ASPIRATION INTO LUNGS. GET MEDICAL ATTENTION IF REQUIRED IN ALL
CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:>-50F,>-46C

Lo

Temperature Limits:29.4C, 85.F

Vapor Pressure:275-437

Vapor Density:>1

Specific Gravity:0.70-0.77

Solubility in Water:SLIGHT

Appearance and Odor:RED-DYED, PINK OR COLORLESS LIQUID; GASOLINE ODOR

Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products:BURNING OR EXCESSIVE HEATING MAY

PRODUCE CARBON MONOXIDE AND OTHER HARMFUL GASES/VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods:IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE IF THE MATERIAL IS A HAZARDOUS WASTE AT THE TIME OF DISPOSAL. CHECK BEFORE DISPOSING TO BE SURE YOU ARE IN COMPLIANCE WITH ALL APPLICABLE LAWS AND REGULATIONS. CHEMTREC/RCRA EMER. NO.:800-424-9346

Disclaimer (provided with this information by the compiling agencies):

This info

mation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.