

PATCH RUBBER COMPANY -- CLEANER FLUID, NON-FLAMMABLE (AEROSOL) -- 2640-00-138-8324

=====
Product Identification
=====

Product ID:CLEANER FLUID, NON-FLAMMABLE (AEROSOL)

MSDS Date:05/26/1989

FSC:2640

NIIN:00-138-8324

MSDS Number: BQNMT

=== Responsible Party ===

Company Name:PATCH RUBBER COMPANY

Box:H

City:ROANOKE RAPIDS

State:NC

ZIP:27870

Country:US

Info Phone Num:(919) 536-2574

Emergency Phone Num

:(919) 536-2574

CAGE:FO808

=== Contractor Identification ===

Company Name:PATCH RUBBER CO

Address:BECKER INDUSTRIAL PARK

Box:H

City:ROANOKE RAPIDS

State:NC

ZIP:27870

Country:US

Phone:919-536-2574/800-424-9300(CHEMTREC)

CAGE:17124

Company Name:PATCH RUBBER COMPANY

Box:H

City:ROANOKE RAPIDS

State:NC

ZIP:27870

Phone:(919) 536-2574

CAGE:FO808

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2

975000
Fraction by Wt: 97%
Other REC Limits:350 PPM (CL)
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:N
TP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE DIZZINESS OR NARCOSIS IN
HIGH VAPOR CONCENTRATIONS. WILL CAUSE DEFATTING OF SKIN. EFFECTS
ARE REVERSIBLE. LONG TERM EXPOSURE VAPOR MAY CAUSE LUNG LIVER OR
KIDNEY DAMAGE. THE SOLVENTS LISTED HAVE BEEN REPORTED TO AFFECT
THE CENTRALNERVOUS SYSTEM.
Explanation of Carcinogenicity:PRESENTLY NOT ON ANY LIST.
Effects of Overexposure:INHALATION - DIFFICULTY IN BREATHING. SKIN -
REDNESS. INGESTION - VOMITING.
Medica
I Cond Aggravated by Exposure:HEART DISEASE, RESPIRATORY
DISORDERS.

=====
===== First Aid Measures =====

First Aid:GIVE OXYGEN - DO NOT INDUCE VOMITING - GASTRIC LAVAGE - WASH
EYES AND SKIN WITH WATER.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:WATER FOG, DRY CHEMICAL, OR CO2.
Fire Fighting Procedures:AEROSOL CANS MAY RUPTURE WHEN HEATED.
Unusual Fire/Exp

losion Hazard:HEATED CANS MAY BURST

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT SWEEPING COMPOUND TO SOAK UP MATERIAL. PUT INTO CONTAINER. DISPOSE AS HAZARDOUS WASTE.

Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.

===== Handling and Storage =====

Handling and Storage Precautions:HEAT, SPARKS, OPEN FLAME AND OTHER SOURCES OF IGNITION. STORE AT TEMPERATURES BELOW 120F.

Other Prec

autions:WHEN SPRAYING MORE THAN ONE HALF CAN CONTINUOUSLY OR ONE CAN CONSECUTIVELY, USE NIOSH APPROVED RESPIRATOR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS IF ABOVE TLV LIMIT EXCEEDING.

Ventilation:LOCAL EXHAUST YES. OTHER TYPES VENTILATION - NONE

Protective Gloves:NONE REQUIRED IF SPRAYING.

Eye Protection:WEAR EYE PROTECTION

Other Protective Equipment:LONG SLEEVE AND LONG PANTS.

Work Hygienic Practice

s:DO NOT SMOKE WHILE USING. WASH HANDS AFTER USING.

Supplemental Safety and Health

KEY2:KT

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:162F,72C

Vapor Pres:100 PSIG

Vapor Density:4.00

Spec Gravity:1.30

Evaporation Rate & Reference: