

SANLO PRODUCTS CO -- MIL-H-46001D-SANWEAR 32/88 -- 9150-00-966-8835

=====
Product Identification
=====

Product ID:MIL-H-46001D-SANWEAR 32/88

MSDS Date:08/01/1992

FSC:9150

NIIN:00-966-8835

MSDS Number: BQQGN

=== Responsible Party ===

Company Name:SANLO PRODUCTS CO

Address:100 ,MANHATTAN AVE SUITE 103

City:UNION CITY

State:NJ

ZIP:07087

Country:US

Info Phone Num:201-348-1684

Emergency Phone Num:201-

348-1684

Preparer's Name:STEVE CULLEN

CAGE:0K5U0

=== Contractor Identification ===

Company Name:SANLO PRODUCTS CO

Address:100 ,MANHATTAN AVE SUITE 103

City:UNION CITY

State:NJ

ZIP:07087

Country:US

Phone:201-348-1684/800-424-9300(CHEMTREC)

CAGE:0K5U0

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC/PETROLEUM
PARAFFINIC BASE

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: >90%

Other REC Limits:NONE RECOMMENDED

OSHA P

EL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:PROPRIETARY ADDITIVES

Fraction by Wt: 500F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, DRY CHEMICAL AND VAPORIZING LIQUID TYPE EXTINGUISHERS. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS OPERATED IN+PRESSURE. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Ex

plosion Hazard:NOT KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. MINIMIZE SKIN CONTACT. KEEP PRODUCT OUT OF SEWERS AND WATERCOURSES BY DIKING OR IMPOUNDING. ADVISE AUTHORITIES IF PRODU CT HAS ENTERED OR MAY ENTER SEWERS, WATERWAYS ETC.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONT

AINER IN COOL PLACE AWAY FROM

EXCESSIVE HEAT, FLAMES & STRONG OXIDIZERS.

Other Precautions:AVOID CONTACT WITH SKIN, EYES, AND CLOTHING. WASH THOROUGHLY AFTER HANDLING. LAUNDRER CLOTHING BEFORE REUSE. AVOID INHALING VAPORS. EMPTY CONTAINERS OF THIS PRODUCT MAY BE HAZARDOUS DUE TO THE RETENTIO N OF RESIDUES AND VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF TLV EXCEED, WEAR A NIOSH-APPROVED SELF CON

TAINED BREATHING APPARATUS. WEAR

SUPPLIED-AIR RESPIRATOR IN CONFINED OR ENCLOSED SPACES, IF NEEDED.

Ventilation:LOCAL EXHAUST FAN IS RECOMMENDED TO MAINTAIN CONCENTRATION OF OIL MIST IN AIR BELOW RECOMMENDED TLV.

Protective Gloves:RUBBER/OIL RESISTANT GLOVES RECOMMENDED

Eye Protection:CHEMICAL SAFETY GOGGLES,FULL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL

HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME
NSN. MANUFACTURER STATES THAT ONE MSDS FOR MIL-H-46001D COVERS ALL
SANWEAR PRODUCTS. ONLY VISCOSITY SLIGHTLY CHANGES.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:525F,274C

Melt/Freeze Pt:M.P/F.P Text:-5F,-21C

Vapor Pres:5

Spec Gravity:0

.90

Viscosity:32 CST @ 40C

Evaporation Rate & Reference: