

EASTMAN KODAK CO -- KODAK RP X-OMAT FIXER & REPLENISHER, PART A -- 6525-01-075-8325
===== Product Identification =====

Product ID:KODAK RP X-OMAT FIXER & REPLENISHER, PART A

MSDS Date:10/14/1991

FSC:6525

NIIN:01-075-8325

MSDS Number: BQQHH

=== Responsible Party ===

Company Name:EASTMAN KODAK CO

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-724-4501

Emerg

ency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 40-45%

Other REC Limits:NONE SPECIFIED

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fractio

n by Wt: 35-40%
Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM THIOSULFATE
CAS:7772-98-7
RTECS #:XN6476000
Fraction by Wt: 10-15%
Other REC Limits:NONE SPECIFIED

Ingred Name:AMMONIUM ACETATE (SASA III)
CAS:631-61-8
RTECS #:AF3675000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BISULFITE (SARA III)
CAS:10192-30-0
RTECS #:WT3595000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM BISULFITE (SASA III)
CAS:7631-90-5
RTECS #:VZ2000000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM ACETATE
CAS:126-96-5
RTECS #:AJ4375000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

==== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT ESTABLISHED.
Routes o

f Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: LOW HAZARD FOR RECOMMENDED HANDLING. SKIN: LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:EYES: NOSPECIFIC HAZARD KNOWN TO EASTMAN KODAK COMPANY. HOWEVER, ANY MATERIAL THAT CONTACTS THE EYE MAY BE IRRITATING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER. SKIN: WASH AFETR EACH CONTACT. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, "A LCOHOL" FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS ANDPROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM CONTACT WITH OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED AND AWAY FROM ACIDS AND BASES.
Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.
Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT TO CONTROL AIRBORNE LEVELS.
Protective Gloves:YNONE SPECIFIED BY MANUFACTURER.NEOPRENE
Eye Protection:SAFETY GLASSES SHOULD BE WORN.
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.
Work

Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

KEY1:C3. THIS IS A 2-PART KIT. FORMULA CHANGED. SEE PNI A FOR PREVIOUS FORMULATION. TYPICALLY 10 ROOM VOLUMES PER HOUR IS CONSIDERED GOOD GENERAL VENTILATION: VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS OF USE.

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 @20C

Vapor Density:0.6

AIR=1

Spec Gravity:1.361

pH:4.10

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS SOLUTION; SLIGHT AMMONIA ODOR.

Percent Volatiles by Volume:45

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE AS WELL AS AMMONIA AND OXIDES OF SULFUR AND NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE AND LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability

for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.