View NSN Online: https://aerobasegroup.com/nsn/6810-00-865-2915

ASHLAND PETROLEUM CO DIV OF ASHLAND OIL INC -- 034015 ALCOHOL-ETHANOL 6810-00-865-2915 Product ID:034015 ALCOHOL-ETHANOL MSDS Date:09/12/1991 FSC:6810 NIIN:00-865-2915 **MSDS Number: BQQND** === Responsible Party === Company Name: ASHLAND PETROLEUM CO DIV OF ASHLAND OIL INC Address:1409 WINCHESTER AVE Box:391 City:ASHLAND State:KY ZIP:41114 Country:US Info Phone N um:606-329-3333 / FAX 606-329-3230 Emergency Phone Num:800-274-5263 CAGE:81355 === Contractor Identification === **Company Name: ASHLAND INC** Address:1409 WINCHESTER AVE Box:391 City:ASHLAND State:KY ZIP:41114 Country:US Phone:800-622-6846 CAGE:81355 Company Name: BASEVIEW PETROLEUM INC Box:265 City:EMERADO State:ND ZIP:58228 Country:US CAGE:5W146 Company Name: VINING OIL CO Address:301 2D AVE NW Box:1197 City: JAMESTOWN State:ND ZIP:58401-3108 Country:US Phone:701-252-0890 CAGE:9V533

====== C

omposition/Information on Ingredients ==========

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 95% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9293

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES Fraction by Wt: 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:100 MG/M3

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES **Reports of Carcinoge** nicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: MAY CAUSE IRRITATION OF EYES, AND MUCOUS MEMBRANES. MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION IF INHALED OR INGESTED. CHRONIC: MAY CAUSE SKIN IRRITATION OR DERMATITIS. MAY CAUSE LIVER DAMAGE. Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN. Effects of Overexposure: INHALATION/INGESTION: DROWSINESS, DIZZINESS, HEADACHE, GIDDINESS, NAUSE A, VOMITING. EYES: REDNESS, TEARING, BLURRED VISION. SKIN: REDNESS, RASH, DRY SKIN. Medical Cond Aggravated by Exposure: PREEXISTING EYE, SKIN, AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. FURTHER IMPAIRMENT OF LIVER FUNCTION MAY OCCUR IF PREEXISTING LIVER DISORDERS EXIST.

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH RESUSCITATION IF NOT BREATHING. GET MEDICAL A TTENTION IMMEDIATELY. EYE: IMMEDIATELY FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING EYELID. G ET MEDICAL ATTENTION IMMEDIATELY. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

Flash Point Method:TCC
Flash Point:55.0F,12.8C
Lower Limits:3.3%
Extinguishing Media:USE WATER FOG, CARBON DIO
XIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FULL FIRE FIGHTING PROTECTIVE EQUIPMENT
AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE
EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

Spill Release Procedures:NOTIFY SAFETY PERSONNEL OF SPILL/LEAK. PROVIDE MAXIMUM EXPLOSION-PROOF V ENTILATION. ELIMINATE ALL SOURCES OF

IGNITION. WEAR PROTECTIVE EQUIPMENT. CONSIDER WATER DILUTION. ABSORB WITH INERT MATERIAL. Neutralizing Agent:NOT APPLICABLE.

Handling and Storage Precautions:PROTECT CONTAINERS FROM PHYSICAL DAMAGE. STORAGE AND USE CONDITIONS MUST BE SUITABLE FOR AN OSHA CLASS IB FLAMMABLE LIQUID.

Other Precautions:MAKE FREQUENT CAREFUL LEAKAGE INSPECTIONS. ISOLATE FROM OXIDEZERS, CHEMIC

ALS CAPABLE OF SPONTANEOUS HEATING, MATERIALS REACTING WITH AIR OR MOISTURE TO LIBERATE HEAT, IGNITION SOURCES AND EXPLOSIVES. KEEP OUT OF DIRECT SUN & AWAY FROM HEAT.

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED RESPIRATORS. RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANT IN AIR & IN ACCORDANCE WITH O SHA (29 CFR 1910.134).
Ventilation:USE BOTH GENERAL AND LOCAL NONSPARKING, EXPLOSION-PROOF EXHAUST VENTILATION TO MAINTAIN AIRBORNE LEVELS BELOW TLV/PEL.
Protective Gloves:WEAR IMPERVIOUS GLOVES
Eye Protection:SAFETY GLASSES/CHEMICAL SAFETY GOGGLES.
Other Protective Equipment:WEAR RUBBER BOOTS, APRONS, AND OTHER APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT SUITABLE TO THE WORK SITUATION.
Work Hygienic Practices:PRACTICE GOOD PERSONAL HYGIENE. KEEP MATERIAL OFF CLOTHES AND EQUIPMENT.
DO NOT SMOKE ANYWHERE NEAR WORK AREA.
Supplemental Safety and Health
NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

HCC:F2 Boiling Pt:B.P. Text:>158F,>70C Melt/Freeze Pt:M.P/F.P Text:-173F,-114C Vapor Pres:45 MM HG Vapor Density:>1 (AIR=1) Spec Gravity:0.79 (WATER=1) Evaporation Rate & amp; Reference:6.8 (ETHYL ETHER=1) Solubility in Water:COMPLE TE Appearance and Odor:COLORLESS, MOBILE LIQUID Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION. DO NOT USE ALUMINUM CONTAINERS FOR STORAGE AT TEMPERATURES > 120F. Hazardous Decomposition Products:CARBON MONOXIDE CAN FORM ON INCOMPLETE COMBUSTION.

====== Disposal Consi

derations ===============

Waste Disposal Methods:MATERIAL SHOULD BE RECLAIMED, RECYCLED OR INCINERATED IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any per son utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.