

DAUBERT -- NOX RUST X-110 -- 8030-00-903-0931

===== Product Identification =====

Product ID:NOX RUST X-110

MSDS Date:01/01/1990

FSC:8030

NIIN:00-903-0931

MSDS Number: BQSGT

=== Responsible Party ===

Company Name:DAUBERT

Address:4700 S CENTRAL AVE

City:CHICAGO

State:IL

ZIP:60638

Country:US

Info Phone Num:312-496-7350

Emergency Phone Num:312-496-7350

Preparer's Name:J KUKSUK

CAGE:DO182

=== Contract

or Identification ===

Company Name:DAUBERT

Address:4700 SOUTH CENTRAL AVENUE

City:CHICAGO

State:IL

ZIP:60638

Phone:312-496-7350/800-424-9300(CHEMTREC)

CAGE:DO182

Company Name:DAUBERT CHEMICAL CO

Address:4700 S CENTRAL AVE

Box:City:CHICAGO

State:IL

ZIP:60638-1531

Country:US

Phone:708-496-7350

CAGE:7X108

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC SOLVENT

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

=====

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE; EXCESSIVE INHALATION MAY PRODUCE DIZZINESS, NAUSEA, HEADACHE, AND UNCOORDINATION. MAY CAUSE REVERSIBLE EYE AND SKIN IRRITATION. BREATHING MISTS MAY CAUSE DIZZINESS OR PULMONARY IRRITATION.

Effects of Overexposure:CHRONIC: PROLONGED SKIN EXPOSURE MAY CAUSE DERMATITIS OR OIL ACNE.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR, CONSULT PHYSICIAN. IF BREATHING IS DIFFICULT GIVE OXYGEN. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. EYES: FLUSH EYES IMMEDIATELY WITH WATER AT LEAST 15 MINUTES. C ONSULT PHYSICIAN. SKIN: WASH WITH SOAP & WATER. IF IRRITATION OR RASH DEVELOPS, CONSULT PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

F

lash Point:100F,38C

Lower Limits:0.7

Upper Limits:5.0

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, AND FOAM. NOTE: FOAM MAY CAUSE FROTHING AND SPATTERING.

Fire Fighting Procedures:USE WATER SPRAY TO COOL CONTAINERS EXPOSED TO FLAMES. FIRE FIGHTING PERSONNEL SHOULD WEAR RESPIRATORY PROTECTION (POSITIVE PRESSURE IF AVAILABLE).

Unusual Fire/Explosion Hazard:PRODUCT OF COMBUSTION INCLUDE FUMES, SMOKE AND CARBON MONOXIDE.

=====
Accidental Release Measures
=====

Spill Release Procedures:SHUT OFF IGNITION SOURCES. CONTAIN SPILL & KEEP FROM ENTERING WATERWAYS OR SEWERS. LARGE QUANTITIES CAN BE PUMPED. SMALL QUANTITIES MAY BE SOAKED UP ON INERT ABSORBENT. CONSULT YOUR SPCC PLAN.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM FLAMES, SPARKS OR HOT SURFACES. NEVER USE A TORCH TO CUT OR WELD ON/NEAR CONTAINER. EMPTY CONTAINERS CAN CONTAIN EXPLOSIVE VAPORS.

O

ther Precautions:NEVER WEAR OIL SOAKED CLOTHING. LAUNDRER OR DRY CLEAN BEFORE WEARING. DISCARD OIL SOAKED SHOES. AFFIX PROPER WARNING LABELS ON CONTAINERS IN ACCORDANCE WITH 29 CFR 1010.1200.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED IF ADEQUATE VENTILATION IS PRESENT. IF EXPOSURE LIMIT IS EXCEEDED, NIOSH/MSHA APPROVED APPARATUS REQUIRED.

Ventilation:PROVIDE ADEQUATE VENTILATION TO CONTROL LEVEL BELOW PER

MISSIBLE EXPOSURE LIMIT.

Protective Gloves:OIL RESISTANT (NEOPRENE OR PLASTIC)

Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment:IF THERE IS A A LIKELIHOOD OF OIL SPLASHING, AN OIL RESISTANT APRON SHOULD BE WORN TO PREVENT CLOTHING CONTAMINATION.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:1.8

Vapor Density:>1

Spec Gravity:0.88

Evaporation Rate & Refer
ence: