

FLEXITALLIC CANADA LTD -- ASBESTOS FILLED SPIRAL-WOUND GASKET -- 5330-00-965-5188

===== Product Identification =====

Product ID:ASBESTOS FILLED SPIRAL-WOUND GASKET

MSDS Date:10/01/1991

FSC:5330

NIIN:00-965-5188

MSDS Number: BQSHM

=== Responsible Party ===

Company Name:FLEXITALLIC CANADA LTD

Address:1337 LOUGAR AVE

City:SARNIA ONT CAN

Country:CA

Emergency Phone Num:519-332-8300

CAGE:0TY31

=== Contr

actor Identification ===

Company Name:FLEXITALLIC CANADA LTD

Address:1337 LOUGAR AVE

Box:City:SARNIA, ONT CAN

Phone:519-332-8300

CAGE:0TY31

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health

Hazards Acute and Chronic:BREATHING OF ASBESTOS FIBERS IN  
SIGNIFICANT AMOUNTS MAY PRODUCE IRREVERSIBLE LUNG DISEASE AND  
CANCER.

Explanation of Carcinogenicity:CONTAINS A [1332-21-4] WHICH IS  
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

===== Fire Fighting Measures =====

Extinguishing Media:DETERMINED BY SURROUNDING MATERIAL, ASBESTOS NOT  
COMBUSTIBLE IN AIR.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM FINES AND DUST, CAREFULLY AVOIDING DUSTING. IF SWEEPING IS USED, CONTROL DUST BY WETTING AREA AND USE APPROPRIATE DUST MASK.

===== Handling and Storage =====

Handling and Storage Precautions:N/A, AS A FINISHED PRODUCT IN SPIRAL WOUND GASKETS.

Other Precautions:SEE OTHER REGULATIONS FOR ASBESTOS HANDLING IN CFR TITLE 29, PART 1910, SUBPART 2, PARA 1910.1001.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MESA/MSA/OSHA RESPIRATOR IF DESIRED.

Ventilation:LOCAL EXHAUST: CONSULT LOCALLY APPLICABLE REGULATIONS FOR EMISSIONS.

Work Hygienic Practices:KEEP WORK AREA CLEAN OF ASBESTOS DUST.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T7

Boiling Pt:B.P. Text:SOLID

Spec Gravity:2.5

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT BLUE WITH NO ODOR.

===== Stability and Reactivity

Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.