

FARWEST PAINT MFG CO -- EXT. TRIM ENAMEL GREEN 14050 LEAD AND CHROM --  
8010-01-333-9438

===== Product Identification =====

Product ID:EXT. TRIM ENAMEL GREEN 14050 LEAD AND CHROM

MSDS Date:09/19/1991

FSC:8010

NIIN:01-333-9438

MSDS Number: BQSQL

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Eme

rgency Phone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 4%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TEXANOL (ESTER

ALCOHOL) (SARA 313)  
CAS:25265-77-4  
RTECS #:UF6000000  
Fraction by Wt: 2%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION, IN  
CONFINED AREAS, MAY LEAD TO MUCOUS MEMBRANE  
IRRITATION-DIZZINESS-HEADACHE. SKIN: IRRITATION. EYE: IRRI  
TATION.  
INGESTION: AMOUNTS INGESTED INCIDENTAL TO CONSUMER AND INDUSTRIAL  
HANDLING ARE NOT LIKELY TO CAUSE INJURY, HOWEVER, INGESTION OF  
LARGER AMOUNTS COULD CAUSE SERIOUS INJURY

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS  
DEVELOP-SEEK MEDICAL ATTN IMMEDIATELY. SKIN: WASH OFF QUICKLY WITH  
PLENTY OF WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE  
REUSE. EYE: FLUSH IMMEDIATELY  
WITH LARGE AMOUNTS OF WATER,  
ESPECIALLY UNDER LIDS, FOR 15 MINUTES. OBTAIN EMERGENCY MEDICAL  
TREATMENT. INGESTION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT  
IMMEDIATELY.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, OR WATER FOG  
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED  
CONTAINERS.  
Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY  
BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND  
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED  
WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP  
FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND  
APPROPRIATELY LABELED.  
Other Precautions:USE ONL

Y WITH ADEQUATE VENTILATION. AVOID BREATHING  
VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW  
APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC  
VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION  
AGAINST MATERIALS.

Ventilation:LOCAL EXHAUST PREFERRABLE. GENERAL EXHAUST IF EXPOSURE TO  
MATERIALS ARE MAI

NTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves:GLOVES RECOMMENDED BY SUPPLIER

Eye Protection:SFTY GLASSES W/UNPERFORATED SIDESHIELDS

Other Protective Equipment:EYE WASH, SAFETY SHOWERS, GOGGLES, SAFETY  
GLASSES, IMPERVIOUS GLOVES.

Work Hygienic Practices:KEEP AREA CLEAN & FREE FROM SPILLS/LEAKS.

ALWAYS WASH HANDS THOROUGHLY W/SOAP & WATER BEFORE HANDLING  
FOOD-DRINK-SMOKING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:23.8 @ 25C

Vapor Density:> THAN AIR

pH:7-8

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT.

Percent Volatiles by Volume:7.5%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH  
OXIDIZING A

GENTS

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL  
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied

, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.