

RIVERSIDE MANUFACTURING CO. -- WINDSHIELD WASHER -- 6850-00-926-2275

=====
Product Identification
=====

Product ID:WINDSHIELD WASHER

MSDS Date:03/21/1994

FSC:6850

NIIN:00-926-2275

MSDS Number: BQWDK

=== Responsible Party ===

Company Name:RIVERSIDE MANUFACTURING CO.

Address:10390 BERMUDA CT

City:MOHAVE VALLEY

State:AZ

ZIP:86440

Country:US

Info Phone Num:602-786-1771

Emergency Phone Num:919-834-00

90

Preparer's Name:LARRY LIVELY

CAGE:MO246

=== Contractor Identification ===

Company Name:RIVERSIDE MANUFACTURING CO.

Address:10390 BERMUDA CT

City:MOHAVE VALLEY

State:AZ

ZIP:86440

Country:US

Phone:602-786-1771

CAGE:MO246

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ALCOHOL (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 50%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:29 CFR 1910.1200

ACGIH TLV:1000 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LB

=====
Hazards Identification
=====

Health Hazards Acute and Chronic: REPEATED EXPOSURE BY INHALATION OR INGESTION MAY CAUSE INTERNAL POISONING OR BRAIN DISORDERS, BLINDNESS.

Effects of Overexposure: MILD SKIN IRRITATION, IRRITATION OF MUCOUS, NAUSEA, GIDDINESS, LIGHT-HEADED.

Medical Cond Aggravated by Exposure: NOT KNOWN

=====
First Aid Measures
=====

First Aid: SKIN & EYE: FLUSH WITH WATER FOR 15 MINUTES. INHALATION:

REMOVE TO FRESH AIR. INGESTION: GIVE LARGE AMOUNTS OF WATER OR MILK, AND INDUCE VOMITING. IF UNCONSCIOUS, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method: TCC

Flash Point: 51.8F, 11.0C

Autoignition Temp: Autoignition Temp Text: 725 F

Lower Limits: 6

Upper Limits: 36

Extinguishing Media: WATER SPRAY, DRY POWDER, FOAM, CO2

Fire Fighting Procedures: METHANOL BURNS W/CLEAN, CLEAR FLAME ALMOST INVI

SIBLE IN DAYTIME. CONCENTRATIONS OF >20% IN WATER CAN

IGNITE, WATER MAY BE INEFFECTIVE DEPENDING ON DEPTH OF METHANOL

Unusual Fire/Explosion Hazard: FIRE FIGHTERS MUST WEAR FULL

FACE, POSITIVE PRESSURE, SELF CONTAINED BREATHING APPARATUS AND APPROPRIATE CLOTHING.

=====
Accidental Release Measures
=====

Spill Release Procedures: ELIMINATE IGNITION SOURCES. STOP SPILL.

CONTAIN BY DIKING. RECOVER OR DILUTE WITH WATER TO REDUCE HAZARD.

Neutralizing Agent: WATER

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN ENCLOSED & GROUNDED EQUIPMENT. NO SMOKING OR OPEN FLAME. ENSURE PROPER ELECTRICAL GROUNDING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED.
Ventilation:LOCAL AND GENERAL
Protective Gloves:NEOPRENE
Eye Protection:FACE SHIELD AND SAFETY GLASSES
Other Protective Equipment:WEAR CHEMICAL RESISTIVE CLOTHING.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:148F,64C
Melt/Freeze Pt:M.P/F.P Text:-144F,-98C
Vapor Pres:96
Vapor Density:1.105
Spec Gravity:0.792
Evaporation Rate & Reference:2.1
Solubility in Water:100%
Appearance and Odor:BLUE/ODORLESS
Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, STRONG ACIDS, STRONG BASES; MAY BE CORROSIVE TO LEAD & ALUMINUM.
Stability Condition to Avoid:DO NOT EXPOSE TO OPEN FLAME.
Hazardous Decomposition Products:FORMALDEHYDE & CARBON MONOXIDE

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States

ates of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.