

STA-LUBE INC -- DEXRON-II MULTI-PURPOSE TRANSMISSION/TRANSA -- 9150-00-698-2382

=====
Product Identification
=====

Product ID:DEXRON-II MULTI-PURPOSE TRANSMISSION/TRANSA

MSDS Date:07/21/1989

FSC:9150

NIIN:00-698-2382

MSDS Number: BQXTQ

=== Responsible Party ===

Company Name:STA-LUBE INC

Address:3039 ANA STREET

City:COMPTON

State:CA

ZIP:90224

Country:US

Info Phone Num:213-537-5650

Emergency Phone

Num:213-664-2121 (LA POISON CENTER)

CAGE:33876

=== Contractor Identification ===

Company Name:STA-LUBE INC

Address:3039 ANA ST

Box:City:RANCHO DOMINGUEZ (PART OF COMPTON)

State:CA

ZIP:90221

Country:US

Phone:310-664-2121/800-424-9300(CHEMTREC)

CAGE:33876

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL

CAS:64741-89-5

RTECS #:PY8041500

Other REC Limits:NONE RECOMMENDED

Ingred Name:REFINED HEAVY PARAFFINIC DISTILLATES

CAS:64741-88-4

Other REC Limits:

NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED CONTACT MAY IRRITATE THE SKIN. EXPOSURE TO FUMES, MISTS, IF GENERATED, MAY IRRITATE THE EYES AND UPPER RESPIRATORY TRACT.
Explanation of Carcinogenicity:NOT A CARCINOGEN.
Effects of Overexposure:
EYE-MAY CAUSE BURNING, TEARING AND REDNESS.
SKIN-PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE BURNING, REDNESS AND DERMATITIS. INHALATION-MAY IRRITATE THE NOSE, THROAT AND UPPER RESPIRATORY TRACT. INGESTION-ACCIDENTALLY SWALLOWING CAN CAUSE IRRITATION OF THE STOMACH AND INTESTINAL TRACT.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN CONDITION.
PRE-EXISTING RESPIRATORY CONDITIONS IF MISTS OR FUMES ARE GENERATED.

===== First Aid Measures =====

First Aid:EYE-FLUSH THE EFFECTED EYE WITH WATER. IF IRRITATION DEVELOPS, SEEK MEDICAL ATTENTION. SKIN-WIPE MATERIAL FROM SKIN. THOROUGHLY WASH SKIN WITH SOAP & WATER. USE A WATERLESS CLEANER, IF NEEDED. BREATHING-MOVE AWAY FROM EXPOSURE TO MISTS OR FUMES INTO FRESH AIR. SWALLOWING-IF VICTIM IS CONSCIOUS AND ALERT, GIVE MILK OR WATER TO DRINK. SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:
COC
Flash Point:>204.4C, 400.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND WATER SPRAY. WATER SPRAY OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR PROTECTIVE EQUIPMENT & CLOTHING WHEN FIGHTING FIRES. USE A SELF-CONTAINED BREATHING APPARATUS FOR FIRES IN ENCLOSED SPACES, USE WATER SPRAY TO COOL CONTNRS
Unusual Fire/Explosion Hazard:THIS MATERIAL CAN IGNITE & BURN WHEN HEATED ABOVE ITS FLASH POINT. EMPTY TANKS OR CONTAINERS RETAIN MATERIAL RESIDUE AND

MAY, IF HEATED, CAN IGNITE & EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR RECOMMENDED PROTECTIVE CLOTHING & EQUIPMENT & PROVIDE ADEQUATE VENTILATION. DO NOT ALLOW SPILLS TO ENTER SEWERS, STREAMS OR SURFACE WATERS. DIKE & CONTAIN SPILL. PICK UP LARGE SPILLS FOR LATER RE CLAMATION & DISPOSAL. USE AN INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:

STORE IN CLOSED CONTAINERS IN A COOL, DRY, WELL-VENTILATED AREA AWAY FROM HEAT AND STRONG OXIDIZING AGENTS. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:OPERATIONS SUCH AS MAINTENANCE, REPAIR, CLEAN-UP, OR SAMPLING INCREASE THE POTENTIAL FOR EXPOSURE TO THIS MATERIAL. PERSONNEL INVOLVED IN THESE TYPES OF OPERATIONS SHOULD WEAR PROTECTIVE EQUIPMENT & C LOTHING & EXERCISE SPECIAL PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Re

spiratory Protection:RESPIRATORY PROTECTION MAY BE NECESSARY TO MINIMIZE EXPOSURE TO MISTS & FUMES. WEAR A NIOSH-APPROVED PARTICULATE RESPIRATOR IN SITUATIONS WHERE MIST CONCENTRATIONS MAY EXCEED RECOMMENDED EXPOSURE LIM I TS.

Ventilation:GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST IS RECOMMENDED TO MAINTAIN MIST OR FUME CONCENTRATIONS BELOW LIMITS.

Protective Gloves:PROTECTIVE GLOVES ARE RECOMMENDED.

Eye Protection:CHEMICAL GOGGLES ARE RECOMMENDED.

Other Protective Equipment:

PROTECTIVE CLOTHING ARE RECOMMENDED TO PREVENT SKIN CONTACT. USE BARRIER CREAMS SPECIFIC FOR PETROLEUM-BASED MATERIAL.

Work Hygienic Practices:AN EYE WASH & A SOURCE OF RUNNING WATER SHOULD BE AVAILABLE TO FLUSH OR WASH THE EYES AND SKIN.

Supplemental Safety and Health

USE SELF-CONTAINED SUPPLIED-AIR RESPIRATORS FOR EMERGENCIES.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>315.6C, 600.F

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Tex

t:NA
Vapor Pres:NEGLIGIBLE
Vapor Density:>AIR
Spec Gravity:0.85-0.95
pH:NA
Viscosity:>100 SUS
Evaporation Rate & Reference:NEGLIGIBLE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:A RED COLORED OILY LIQUID WITH A PAINT PETROLEUM
ODOR.
Percent Volatiles by Volume:NEGL
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
INCOMPATIBLE WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE SPECIFIED BY
MANUFACTURER.
Hazardous Decomposition Products:BURNING PRODUCES CARBON DIOXIDE,
CARBON MONOXIDE & POSSIBLE TRACE AMOUNTS OF OXIDES OF SULFUR AND
NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL REGULATIONS. EMPTY TANKS & CONTAINERS SHOULD BE COMMERCIALY
CLEANED AND RECONDITIONED BEFORE REUSE.

Disclaimer (provided with this information by the compiling agencies):

This
information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.