

DEFT INC CHEMICAL COATING DIV -- CAT, 1-COAT, TT-P-2756, 34097 PC 03 GN 226 --
8010-01-353-3693

===== Product Identification =====

Product ID:CAT, 1-COAT, TT-P-2756, 34097 PC 03 GN 226

MSDS Date:12/21/1992

FSC:8010

NIIN:01-353-3693

Kit Part:Y

MSDS Number: BQYQP

=== Responsible Party ===

Company Name:DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Coun

try:US

Info Phone Num:714-474-0400

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:NORM GAUL

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC ISOCYANATE

CAS:28182-81-2

RTECS #:HQ9170000

Fraction by Wt: 60%

Other REC Limits:NONE SPECIFIED

Ingred Name:ETHYL-3-ETHOXYPROPIONATE

CAS:763-69-9
RTECS #:UF3325000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED

Ingred Name:N-BUTYL ACETATE
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM/STEL 200 PPM
ACGIH TLV:150 PPM/STEL 200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 400 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:N
O

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: VAPORS ARE IRRITATING TO EYES,
NOSE, & THROAT. INHALATION MAY CAUSE HEADACHES, DIFFICULT BREATHING
AND LOSS OF CONSCIOUSNESS. CHRONIC: AS A RESULT OF OVEREXPOSURE OR
SINGLE LARGE DOSE, SOME INDIVIDUALS MAY DEVELOP ISOCYANATE
SENSITIZATION WHICH MAY LATER CAUSE THEM TO REACT TO EXPOSURE OF
ISOCYANATE LEVELS.

Effects of Overexposure:INHALATION: HEADACHE, DIZZINESS, STAGGERING
GAI

T, CONFUSION, UNCONSCIOUSNESS OR COMA. EYES: LIQUID, AREOSOLS,
VAPORS TEARING, REDNESS, SWELLING, STINGING. SKIN: ISOCYANATES
REACT W/SKIN PROTEIN & MOIS TURE, IRRITATING. RASH. SKIN
ABSORPTION: DRYING, SKIN CRACK.INGESTION: MOUTH/STOMACH CORROSIVE.
DO NOT INDUCE VOMITING.

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY
DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMITITIS. ISOCYANATE
SENSITIZATION.

=====
===== First Aid Measures =====

=====

First Aid:INHALATION: REMOVE TO FRESH AIR. ARTIFICIAL RESPIRATION AS NEEDED. ASTHMATIC TYPE SYMPTOMS. GET MEDICAL ATTENTION. SKIN: WASH AFFECTED AREAS WITH SOAP & WATER. REMOVE & WASH CONTAMINATED CLOTHING BEFO RE REUSE. EYES: FLUSH FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Metho

d:TCC

Flash Point:76.0F,24.4C

Lower Limits:1.05%

Upper Limits:7.60%

Extinguishing Media:FOAM,DRY CHEMICAL,WATER FOG,CO2,ALCOHOL FOAM.

Fire Fighting Procedures:H2O TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP, AUTO IGNITION/EXPLOSION. DURING A FIRE HDI VAPORS MAY BE GENERATED BY COMBUSTION OR THERMAL DECOMP.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, SPARKS, ELECTRICAL STATIC. MAY EXPLODE WHEN EXPOSED TO HEAT. OVEREXPOSURE TO DECOMPOSITION PRODUCTS HEALTH HAZARD. N

OT IMMEDIATELY APPARENT

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106 AVOID STORING NEAR HEAT, FIRE, FLAMES, SPARKS.

STORE IN WELL VENTILATED AREAS.TIGHTLY CLOSED.

Other Precautions:KEEP UPRIGHT TO PREVENT LEAKAGE. PREVENT PROLONGED BREATHING. PROLONGED OVEREXPOSURE ALLERGIC REACTION. AVOID CONTACT WITH SKIN & EYES. DO NOT TAKE INTERNALLY. WASH HANDS BEFORE EATING OR SMOKING OR U SING WASHROOM. SMOKE IN DESIGNATED AREAS

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OBSERVE OSHA REGUALTIONS FOR RESPIRATOR. PROPER VENT

ILATION. KEEP EXPOSURE LEVELS DOWN AND AIR VAPORS.

Ventilation: AIRBORNE CONCENTRATIONS OF SOLVENT, HDI & POLYISOCYANATED
BELOW TLV'S. REMOVE ALL IGNITION SOURCES. HEAT, FLAME, SPARKS.

Protective Gloves: COTTON, NEOPRENE, RUBBER, POLYETHYLENE.

Eye Protection: SAFETY/CHEMICAL GOGGLES, FULL-FACE SHIELD

Other Protective Equipment: THE USE OF LONG SLEEVE & LONG LEG CLOTHING
IS RECOMMENDED. REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

=====
Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: 260 TO 401F

Vapor Density: > AIR

Spec Gravity: 1.03121

Evaporation Rate & Reference: .47

Solubility in Water: INSOLUBLE

Appearance and Odor: AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume: 41.7

=====
Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE
ACTIVE MATERIALS.

Stability Condition to Avoid:

CONTACT WITH MOISTURE, MATERIAL WHICH
REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products: BY HIGH HEAT/TEMPERATURE: CARBON
MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND
HDI.

=====
Disposal Considerations =====

Waste Disposal Methods: WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH
FEDERAL, STATE, & LOCAL REGULATIONS. EMPTY CONTAINERS MUST BE
HANDLED WITH CARE, DUE TO PRODUCT RESIDUE AND FLAMMABLE
VAPOR DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability

ty of this information to their particular situation.