View NSN Online: https://aerobasegroup.kr/nsn/8040-01-046-5061

LOCTITE CORP AUTOMOTIVE & CONS -- 44581 FAST CURE EPOXY 45 PART A

MSDS Safety Information

FSC: 8040

NIIN: 01-046-5061 MSDS Date: 03/26/1991 MSDS Num: BRBNM

Product ID: 44581 FAST CURE EPOXY 45 PART A

MFN: 01

Responsible Party Cage: DO429

Name: LOCTITE CORP AUTOMOTIVE & amp; CONSUMER GROUP

Address: 4450 CRANWO

OD CT

City: CLEVELAND OH 44128-4004 Info Phone Number: 216-663-3011

Emergency Phone Number: 800-321-9188 Preparer's Name: KATHRYN A. HOLEN

Review Ind: Y Published: Y

Preparer Co. when other than Responsible Party Co.

Cage: DO429 Assigned Ind: Y

Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP

Address: 4450 CRANWOOD COURT

City: CLEVELAND OH 44128

Cage: DO429

Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP

Address: 4450 CRANWOOD COURT

City: CLEVELAND OH 44128

Phone: (216) 663-3011

Cage: 62377

Name: PERMATEX INDUSTRIAL

Address: HARTFORD SQUARE N 10 COLUMBUS BLVD

City: HARTFORD CT 06106

Phone: 877-376-2839

Item Description Information

lt

em Manager: GSA Item Name: ADHESIVE

Unit of Issue: KT UI Container Qty: 0

Ingredients

Cas: 25068-38-6 RTECS #: KD4380000

Name: BISPHENOL A DIGLYCIDYL ETHER RESIN, EPOXY RESIN, ARALDITE

6004, 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN

% Wt: 45-50

Cas: 1344-28-1

RTECS #: BD1200000

Name: ALUMINUM OXIDE, BAUXITE, ALUMINA, DIALUMINUM TRIOXIDE

% Wt: 45-5

% VVI. 45-

OSHA PEL: 15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

Cas: 13463-67-7 RTECS #: XR2275000

Name: TITANIUM DIOXIDE, TIO2

% Wt: 5-10

OSHA PEL: 15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

Cas: 7631-86-9

RTECS #: VV3100000

Name: SILICON DIOXIDE, CELITE 322

% Wt: 1-3

OSHA PEL: 80 MG/CUM ACGIH TLV: 0.2 MG/CUM

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: EYES: IRRITATION. SKIN: SENSITIZATION OR DERMATITIS.

INHALATION: PULMONARY EFFECTS. Explanation Of Carcinogenicity: NONE

First Aid: INGESTION: INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. SKIN:

WASH THOROUGHLY W/SOAP & DATER. EYES: FLUSH W/WATER FOR 15 MIN. OBTAIN

MEDICAL ATTENTION IN ALL CASES.

===== Headling and Diagonal
Handling and Disposal
Spill Release Procedures: SOAK UP W/INERT ABSORBENT. Waste Disposal Methods: LANDFILL OR INCINERATE IN ACCORDANCE W/LOCAL, FEDERAL & Disposal REGULATIONS.
Handling And Storage Precautions: STORE <110F TO PRESERVE SHELF LIFE. AVOID CONTACT W/EYES & Dr. SKIN.
Fire and Explosion Hazard Information
Flash Point Method: TCC Flash Point Text: >200F Extinguishing Media: CO2, FOAM OR DRY CHEMICAL
Control Measures
Ventilation: SUFFICIENT TO MAINTAIN VAPOR CONCENTRATION BELOW TLV. Protective Gloves: RUBBER OR PLASTIC Eye Protection: SAFETY GLASSES Supplemental Safety and Health: INHALATION OF PURE SILICON DIOXIDE DUST HAS BEEN SHOWN TO CAUSE PULMONARY EFFECTS.
======================================
B.P. Text: >300F Vapor Pres: <5 Solubility in Water: SLIGHT Appearance and Odor: WHITE & BLACK PASTE; MILD ODOR.
Reactivity Data
Stability Indicator: YES Hazardous Polymerization Indicator: NO
Toxicolo gical Information
Ecological Information
MSDS Transport Information
======================================

==========

Other Information

HAZCOM Label

Product ID: 44581 FAST CURE EPOXY 45 PART A

Cage: DO429 Assigned IND: Y

Company Name: LOCTITE CORP AUTOMOTIVE & DONSUMER GROUP

Street: 4450 CRANWOOD COURT

City: CLEVELAND OH

Zipcode: 44128

Health Emergency Phone: 800-321-9188

Label Required IND: Y

Date

Of Label Review: 06/01/1993

Status Code: C

Label Date: 06/01/1993
Origination Code: F
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: EYES: IRRITATION. SKIN: SENSITIZATION OR DERMATITIS.

INHALATION: PULMONARY EFFECTS. TARGET ORGANS: SKIN, LUNGS.

TH. TARGET ORGANS: CENTRAL NERVOUS SYSTEM, KIDNEYS, HEART, BRAIN, BLO OD,

SKIN. C

ARCINOGEN: SILICA DIOXIDE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons co

ntracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.