View NSN Online: https://aerobasegroup.kr/nsn/6550-01-261-5883

EM DIAGNOSTIC SYSTEMS INC -- 660 MAY-GRUNWALD STAIN -- 6550-01-261-5883

Product ID:660 MAY-GRUNWALD STAIN

MSDS Date:11/01/1989

FSC:6550

NIIN:01-261-5883

MSDS Number: BRCCX === Responsible Party ===

Company Name: EM DIAGNOSTIC SYSTEMS INC

Address:480 DEMOCRAT RD

City:GIBBSTOWN

State:NJ ZIP:08027 Country:US

Info Phone Num:609-423-6300 Emergency Phone Num:609-423-630

0

CAGE:0GDF9

=== Contractor Identification ===

Company Name: EM SCIENCE, A DIVISION OF EM INDUSTRIES

Address:480 DEMOCRAT RD

Box:70

City:GIBBSTOWN

State:NJ ZIP:08027 Country:US

Phone:856-423-6300

CAGE:0GDF9

======= Composition/Information on Ingredients ========

Ingred Name: METHANOL (METHYL ALCOHOL), COLUMBIAN SPIRITS

CAS:67-56-1

RTECS #:PC1400000 Fraction by Wt: 99%

Other REC Limits:200 PPM OSHA PEL:260 MG/CUM

ACGIH TLV:262 MG/CUM (SKIN)

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

======================================
LD50 LC50 Mixture:LDLO ORAL (HUMAN): 340 MG/KG Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INGESTION/INHALATION: DEATH W/AS AS LITTLE AS 30 ML. EYES/SKIN: IRRITATION. MAY ALSO CAUSE BLINDNESS & CNS EFFECTS. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, HEADACHE, DRUNKENESS, DROWSINESS, BLURRED VISION.
======================================
First Aid:EYES: WASH W/LARGE AMOUNTS OF WATER. SKIN: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NECESSARY. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Flash Point Method:OC Flash Point:51.19F Lower Limits:6 Upper Limits:36.5 Extinguishing Media:ALCOHOL FOAM, DRY CHEMICAL, CO2 Fire Fighting Procedures:METHYL ALCOHOL WILL ATTACK SOME FORMS OF PLASTIC, RUBBER & COATINGS. MAY ALSO REACT W/METALLIC ALUMINUM AT HIGH TEMPERATURES. Unusual Fire/Explosion Hazard:MODERATE HAZARD WHEN EXPOSED TO FLAME. VIOLENT REACTIONS W/CHROMIC OXIDE (IODINE + ETHANOL + MERCURIC OXIDE), LEAD PERCHLORATE, PERCHLORIC ACID. (SEE SUPP) ==================================
======================================
Handling and Storage Precautions:STORE IN A COOL TEMPERATURE CONTROLLED AREA. KEEP AWAY FROM OPEN FLAME. KEEP CONTAINER CLOSED. USE W/ADEQUATE VENTILATION. Other Precautions:KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAME. AVOID CONTACT W/EYES, SKIN, CLOTHING & BREATHING OF VAPORS.
======= Exposure Controls/Personal Protecti

Ventilation:LOCAL EXHAUST/HOOD Protective Gloves:RECOMMENDED Eye Protection:SAFETY GOGGLES

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

UNUSUAL FIRE CONT'D: PHOSPHORUS TRIOXIDE (POTASSIUM HYDROXIDE + CHLOROFORM), (SODIUM HYDROXIDE + CHLOROFORM).

======== Physical/Chemical Properties ==========

Boiling Pt:B.P. Text:148.28F

Melt/Freeze Pt:M.P/F.P Text:-144.4

F

Vapor Pres:100 Vapor Density:1.11 Spec Gravity:0.791

Evaporation Rate & Reference: (BU AC = 1): 5.9

Solubility in Water:MISCIBLE

Appearance and Odor:SLIGHT ALCOHOLIC ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, PLASTIC RUBBER, COATINGS, METALLIC ALUMINUM.
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, HIGH TEMP.
Hazardous Decomposition Products:FORMALDEHYDE, CO & TOXIC GASES.

Disposal Considerations =========

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent

professional advice to verify and assume responsibility for the suitability of this information to their particular situation.