

SPRAYON PRODUCTS -- 00601 RED INSULATING VARNISH -- 5970-00-785-4098

=====  
Product Identification  
=====

Product ID:00601 RED INSULATING VARNISH

MSDS Date:12/01/1992

FSC:5970

NIIN:00-785-4098

MSDS Number: BRDJW

=== Responsible Party ===

Company Name:SPRAYON PRODUCTS

Address:26300 FARGO AVE

City:BEDFORD HEIGHTS

State:OH

ZIP:44146-1310

Country:US

Info Phone Num:216-292-7400

Emergency Phone Num:216-29

2-7400

CAGE:09800

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 14%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIAN; 9293

Ingred Name:ISOBUTANE

CAS:75-28-5

RTECS #:TZ

4300000  
Fraction by Wt: 14%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 17%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA, LIGHT AROMATIC  
CAS:64742-95-6  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM 9091

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA I  
II)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 18%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 18%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES

Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:OVEREXPOSURE: IRRITATION OF EYES, SKIN AND RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH.

Explanation of Carcinogenicity:2-ETHOXYETHANOL IS CONSIDERED AN ANIMAL TERATOGEN.

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE T

O VAPORS OR

SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:IF INHALED-IF EFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. IF ON SKIN-WASH EFFECTED AREA THOROUGHLY WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRY BEFORE REUSE. IF IN EYES-FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. IF SWALLOWED-DO NOT GIVE ANYTHING IF UNCONSCIOUS. DO NOT INDUCE VOMITING. GIVE SEVERAL GLASSES OF WATER. SEE DOC.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: