

CONOCO INTERNATIONAL INC -- GASOLINE, UNLEADED -- 9130-00-148-7104

===== Product Identification =====

Product ID:GASOLINE, UNLEADED

MSDS Date:10/08/1993

FSC:9130

NIIN:00-148-7104

MSDS Number: BRGGX

=== Responsible Party ===

Company Name:CONOCO INTERNATIONAL INC

Address:5 GREENWAY PLAZA EAST

Box:2197

City:HOUSTON

State:TX

ZIP:77001

Country:US

Info Phone Num:713-293-5550

Emergency Phone Num:800-441-

3637/800-424-9300CHEM,TRANS

Preparer's Name:MSDS ADMINISTRATOR

CAGE:EO213

=== Contractor Identification ===

Company Name:CONOCO INC

Address:5 GREENWAY PLAZA E

Box:2197

City:HOUSTON

State:TX

ZIP:77252

Country:US

Phone:713-293-5550PRODUCT/ 800-4413637MED

CAGE:5R396

Company Name:CONOCO INTERNATIONAL INC

Address:5 GREENWAY PLAZA EAST

Box:2197

City:HOUSTON

State:TX

ZIP:77001

Country:US

Phone:713-293-5550

CAGE:EO213

===== Composition/Information on Ingredients =====

Ingred Name:GAS

OLINE (CONTAINING INGREDIENTS #2 THRU 8)

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM/500 STEL

ACGIH TLV:300 PPM/500STEL;9293

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 0.1-4.9%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1PPM/5STEL;1910.1028

ACGIH TLV:10 PPM; A2; 9293

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 2%

Other REC L

imits:NONE RECOMMENDED

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 15%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 12%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/150 STEL

ACGIH T

LV:100 PPM/150STEL;9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CUMENE (SARA III)

CAS:98-82-8

RTECS #:GR8575000

Fraction by Wt: 1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)/PSEUDOCUMENE

CAS:95-63-6

RTECS #:DC3325000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:25 PPM

ACGIH TLV:25 PPM; 9293

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)

CAS

:1634-04-4

RTECS #:KN5250000

Fraction by Wt: 0-15%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:NOT GIVEN

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:MAY CAUSE EYES, SKIN & LUNG IRRIT

AFTER PROLONGED/REPEATED EXPOSURE. EXTREME EXPOSURE/ASPIRATION INTO LUNGS MAY CAUSE LUNG DAMA

GE OR DEATH. CHRONIC CONTACT MAY CAUSE

DERM. CONTAINS BENZENE WHICH MAY CAUSE LEUKEMIA & BE TOXIC TO BLOOD & BLOOD FORMING TISSUES. CONTAINS MTBE WHICH ODOR MAY CAUSE INDIGESTION & ABOVE SYMPTO

Explanation of Carcinogenicity:CONTAINS B [71-43-2] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, LUNG

IRRITATION, WEAKNESS, HEADACHE, NAUSEA, VOMITING, CONFUSION, BLURRED VISION, DROWSINESS, DIZZINE

SS, SLURRED SPEECH, FLUSHED
FACE, UNCONSCIOUSNESS OR CONVULSIONS.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE
AGGRAVATED BY EXPOSURE.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.NOT BREATH GIVE ART RESP.DIFFICULTY
BREATH GIVE OXYGEN.CALL DR.SKIN:WASH THOROUGHLY W/SOAP & WATER
AFTER HANDLING.IRRIT DEVELOPS SEE DR.EYES:IMMED FLUSH W/PLENTY OF
WATER FOR @ LEAST 15MINS.CALL DR.INGEST:DO NOT
INDUCE VOMIT.IMMED
GIVE 2 GLASSES OF WATER.CALL A DR.ACTIVATED CHARCOAL MIXTURE (50G
CHARCOAL/400ML WATER)MAY BE GIVEN.ADMINISTER 5ML/G OR 350ML FOR AVG
ADULT.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:-50F,-46C
Autoignition Temp:Autoignition Temp Text:536F
Lower Limits: 1
Spec Gravity:0.7-0.77
Solubility in Water:SLIGHTLY SOLUBLE.
Appearance and Odor:RED-DYED LIQUID, GASOLINE ODOR.
Percent Volatiles by Volume:100 %

==

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
INCOMPATIBLE OR CAN REACT WITH STRONG OXIDIZERS.
Stability Condition to Avoid:AVOID UNDUE EXPOSURE TO AIR. AVOID HEAT,
SPARKS AND FLAME.
Hazardous Decomposition Products:CARBON MONOXIDE MAY BE FORMED FROM
INCOMPLETE COMBUSTION. ALSO CARBON DIOXIDE AND OTHER TOXIC
MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:TREATAMENT

/STORAGE/TRANSP/DISPOSAL MUST BE IAW

APPLICABLE LOC/STATE/FED REGS.DO NOT FLUSH TO SURFACE WATER OR
SANITARY SEWER SYSTEM.BY ITSELF LIQ IS EXPECTED TO BE RCRA IGN HAZ
WASTE.REPORT TO NAT RES P CNTR 800-424-8802 IF MATL ENTERS
NAVIGABLE WATER

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants
this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.