

CON-LUX COATINGS, INC. -- VARNISH, SPAR, WATER RESISTING -- 8010-00-160-5852
===== Product Identification =====

Product ID:VARNISH, SPAR, WATER RESISTING

MSDS Date:02/01/1993

FSC:8010

NIIN:00-160-5852

MSDS Number: BRGRN

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-287-4000

Emergenc

y Phone Num:201-287-4000

Preparer's Name:ED DOENGES

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (STODDARD SOLVENT)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 43.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

=====

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE; IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT. CHRONIC; RESPORTS ASSOCIATE PROLONGED OVEREXPOSURE W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Effects of Overexposure:HEADACHE, NAUSEA, DIZZINESS

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR. RESTORE RESPIRATION, IF NECESSARY, TREAT SYMPTOMATICALLY. EYE CONTACT: FLUSH IMMEDIATELY WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point:105F,41C
Lower Limits:1.0
Upper Limits:6.0

Extinguishing Media:CO2, DRY CHEMICAL
Fire Fighting Procedures:USE SCBA. WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS AND COOLING CONTAINERS EXPOSED TO HEAT AND FLAMES.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR APPROPRIATE PERSONAL PROTECTION EQUIPMENT AND APPROVED RESPIRATOR. CONTAIN SPILL AND PUT IN VAPOR TIGHT CONTAINERS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN AREAS TO COMPLY WITH ANSI-NFPA 30 FLAMMABLE AND COMBUSTIBLE LIQUIDS CODE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE APPROVED NIOSH/MSHA ORGANIC VAPOR RESPIRATOR.
Ventilation:SUFFICIENT VENTILATION IN VOLUME AND PATTERN REQUIRED TO KEEP HAZARDOUS MATERIALS BELOW APPLICABLE EXPOSURE LEVELS.
Protective Gloves:NEOPRENE
Eye Protection:SPLASH SHIELDS
Work Hygienic Practices:WASH HANDS PRO

PERLY BEFORE EATING, SMOKING OR
USING WASHROOM FACILITIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:323F,162C

Vapor Pres:2

Vapor Density:>1

Spec Gravity:0.895

Viscosity:E-H GARDNER

Appearance and Odor:CLEAR LIQUID - ALIPHATIC ODOR

Percent Volatiles by Volume:49.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Con

dition to Avoid:HEAT, OPEN FLAME

Hazardous Decomposition Products:CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL REGULATIONS. D001, IGNITABLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants t
his information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.