View NSN Online: https://aerobasegroup.kr/nsn/6850-00-181-7933

INDUSTRIAL TERMINAL SYSTEMS -- ANTIFREEZE, ETHYLENE GLYCOL, INHIBITED

6850-00-181-7933

Product ID:ANTIFREEZE, ETHYLENE GLYCOL, INHIBITED

MSDS Date:07/01/1991

FSC:6850

NIIN:00-181-7933

MSDS Number: BRGRW === Responsible Party ===

Company Name: INDUSTRIAL TERMINAL SYSTEMS

Address:LOGAN FERRY RD City:NEW KENSINGTON

State:PA

ZIP:15068-9318

Country:US

Info Phone Num

:708-559-2000

Emergency Phone Num:708-559-2000 800-424-9300(CHEMTREC)

Preparer's Name: MICHAEL T. BUSCHEK

CAGE:8H406

=== Contractor Identification ===

Company Name: HI-PORT INDUSTRIES INC

Address:409 E. WALLISVILLE ROAD

Box:755

City:HIGHLANDS

State:TX

ZIP:77562-3827

Country:US

Phone:713-426-3541(CHEMTREC 800-424-9300)

CAGE:9N129

Company Name: INDUSTRIAL TERMINAL SYSTEMS

Address:LOGAN FERRY RD Box:City:NEW KENSINGTON

State:PA

ZIP:15068-9318 Country:US CAGE:8H406

Company Name: OLD WORLD INDUSTRIES, INC

(708-559-2000) CAGE:0V3B1 Company Name:VALDES G ENTERPRISES INC Address:627 S VERMONT Box:City:PALATINE State:IL ZIP:60067-6949 Country:US CAGE:3J032
======= Composition/Information on Ingredients ========
Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 90-95% OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB
Ingred Name:DIETHYLENE GLYCOL CAS:111-46-6 RTECS #:ID5950000 Fraction by Wt: 0-5% ACGIH TLV:25 PPM
= ====================================
LD50 LC50 Mixture:ACUTE ORAL LD50 (RAT) IS 5840 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:THIS ITEM MAY BE DERMALLY ABSORBED.MAY CAUSE IRRITATION AND DEFATTING.INGEST:MAY CAUSE GI TRACT IRRITATION.INHAL:MAY CAUSE RESPIRATORY IRRITATION. Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA. Effects of Overexposure:SKIN:DERMATITIS.EYES:REDNESS,TEARING,BLURRED VISION.INGEST:NAUSEA,VOMITING,DIARRHEA. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================

First Aid:INHALATION: REMOVE TO FRESH AIR. CALL A PHYSICIAN IF DISCOMFORT PERSISTS. EYE: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES. CALL A

PHYSICIAN. SKIN: WASH WITH PLENTY OF SOAP & WATER. REM OVE CONTAMINATED CLOTHING/SHOES. INGESTION: IF CONSCIOUS, GIVE 2 GLASSES OF WATER TO DRINK AND INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. CALL A PHYSICIAN IMMEDIATELY. Flash Point Method:TOC Flash Point:245F.118C Autoignition Temp: Autoignition Temp Text: 750F Lower Limits:1.5 Extinguishing Media:NFPA CLASS B EXTINGUISHERS FOR CLASS 111 B LIQUID FIRES (DRY CHEMICAL, FOAM, OR CARBON DIOXIDE) Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE ON FIRE BUT CAN PROTECT FIRE FIGHTERS AND COOL CLOSED CONTAINERS. USE FOG NOZZLES IF WATER IS USED. Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT. APPLYING TO HOT SURFACE REQUIRES SPECIAL PRECAUTIONS. EMPTY CONTAINER VERY HAZARDOUS. ======== Accidental Release Measures ============ Spill Release Procedures: SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY); PLACE COLLECTED MATERIEL IN AN APPROPRIATE CONTAINER FOR DISPOSAL; CLEAN SPILL AREA TO REMOVE SLIPPERINESS. Neutralizing Agent:NONE ============= Handling and Storage ========================== Handling and Storage Precautions: EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUE; DISPOSE OF PROPERLY. FOLLOW LABEL INSTRUCTIONS. Other Precautions: DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOI D CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: USE A NIOSH APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Ventilation: USE LOCAL EXHAUST.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment: APRON AND FOOTWEAR IMPERVIOUS TO THIS MATERIAL. PROVIDE EYE WASH STATION.

Work Hygienic Practi

ces:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health NONE

======== Physical/Chemical Properties ==========

HCC:V5

Boiling Pt:B.P. Text:339F,171C

Vapor Pres:0.4 Vapor Density:2.1 Spec Gravity:1.12 pH:9-11.5

Solubility in Water: APPRECIABLE

Appearance and Odor:GREEN LIQUID WITH MILD ODOR

Percent Volatiles by Volume:97

===== Stability and Reactivity Data =====

=========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OXIDIZERS AND OPEN FLAMES

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

======= Disposal Considerations ============

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated

for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.