

SAF-T-LOK CORPORATION -- SEALING COMPOUND -- 8030-00-952-2205

===== Product Identification =====

Product ID:SEALING COMPOUND

MSDS Date:05/01/1993

FSC:8030

NIIN:00-952-2205

MSDS Number: BRKJR

=== Responsible Party ===

Company Name:SAF-T-LOK CORPORATION

Address:300 EISENHOWER LANE

City:LOMBARD

State:IL

ZIP:60148

Country:US

Info Phone Num:708-971-2001

Emergency Phone Num:708-971-2001

Preparer's Name

:ENVIRONMENTAL HLTH & SFTY

CAGE:JO970

=== Contractor Identification ===

Company Name:SAF-T-LOK CHEMICAL CORPORATION

Address:300 EISENHOWER LANE NORTH

City:LOMBARD

State:IL

ZIP:60148

Country:US

Phone:708-971-2001

CAGE:4Z400

Company Name:SAF-T-LOK CORPORATION

Address:300 EISENHOWER LANE

City:LOMBARD

State:IL

ZIP:60148

Country:US

Phone:708-971-2001

CAGE:JO970

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS MATERIAL

Other REC Limits:NONE SPECIFIED

==

=====  
Hazards Identification  
=====

Health Hazards Acute and Chronic:ORGANIC PEROXIDE HAS BEEN REPORTED TO CAUSE TUMORS IN EXPERIMENTAL ANIMALS WHEN INJECTED UNDER THE SKIN. THE LOW CONCENTRATION (5%) CONTAINED IN THE PRODUCT SHOULD PRESENT NO DANGER WHEN USED PROPERLY UNDER NORMAL CONDITIONS.

Explanation of Carcinogenicity:SACCHARIN, REPORTED TO CAUSE TUMORS IN ANIMALS (250F,>121C

Autoignition Temp:Autoignition Temp Text:>350F

Extinguishing Media

:CO2, FOAM, DRY CHEMICALS

Fire Fighting Procedures:AIR MASK AND PROCEDURES FOR FIGHTING CHEMICAL FIRES

Unusual Fire/Explosion Hazard:CONTAINS ORGANIC PEROXIDE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:PROVIDE GOOD VENTILATION. AVOID EYE AND SKIN CONTACT. SOAK UP SPILL WITH EARTH, SAND, OR ABSORBENT PRODUCT (ZORBAL). RECOVER IN CONTAINER.

=====  
Handling and Storage  
=====

Handling and Storage Prec

autions:STORE BELOW 80 F FOR PROLONGED SHELF LIFE. STORE IN ORIGINAL CONTAINER.

Other Precautions:AVOID PROLONGED SKIN CONTACT.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NOT NORMALLY NECESSARY, BUT PRODUCT SHOULD BE USED IN AREAS OF GOOD VENTILATION.

Ventilation:LOCAL EXHAUST: YES.

Protective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. Text:>300F,>149C

Decomp Temp:Decomp Text:>350F,>177C

Vapor Pres: