View NSN Online: https://aerobasegroup.kr/nsn/6850-01-073-0659 MULTIGRAPHICS -- DEGLAZING SOLVENT -- 6850-01-073-0659 ============ Product Identification ========================= Product ID:DEGLAZING SOLVENT MSDS Date:05/01/1992 FSC:6850 NIIN:01-073-0659 MSDS Number: BRKTR === Responsible Party === Company Name: MULTIGRAPHICS Address:1800 W CENTRAL ROAD City:MT.PROSPECT State:IL ZIP:60056-2293 Country:US Info Phone Num:708-870-5121 Emergency Phone Num:708-870-5121 (DAY) 398-1900 (NIGHT CAGE:09177 === Contractor Identification === Company Name: AM MULTIGRAPHICS Address:4301 W. BROAD STREET Box:City:RICHMOND State:VA ZIP:23230-3394 Country:US Phone:804-353-0111 **CAGE:1A714** Company Name: AM MULTIGRAPHICS DIV OF AM INTL INC Address:431 LAKEVIEW CT Box:City:MOUNT PROSPECT State:IL

ZIP:60056-6048 Country:US

Phone:847-375-1700

CAGE:09177

======= Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

CAS:71-55-6

RT

ECS #:KJ2975000 Fraction by Wt: 96%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

Ingred Name:2-METHYL-2-PROPANOL

CAS:75-65-0

RTECS #:EO1925000 Fraction by Wt: 2-4%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100PPM 9394

Ingred Name: DIMETHOXYMETHANE

CAS:109-87-5

RTECS #:PA8750000 Fraction by Wt: 2-4%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1000 PPM ACGIH TLV:1000 PPM

======= Haz ards Identification ==========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: EYE IRRITANT. SKIN: MILDLY

IRRITATING TO SKIN. INHALE: SLIGHTLY TOXIC, ANESTHETIC EFFECTS MAY OCCUR IN RANGES OF 1000PPM. INGESTION: NOT SIGNIFICANTLY TOXIC.

Explanation of Carcinogenicity: NOT FOUND IN IARC, NTP OR OSHA.

Effects of Overexposure: SKIN: WILL DEFAT SKIN.

Medical Cond Aggravated by Expo

sure:INCREASED SENSITIVITY TO ADRENALINE

MAY BE CAUSED BY OVEREXPOSURE.

First Aid:EYE: FLUSH IMMEDIATELY WITH COPIOUS AMOUNTS OF WATER. SKIN: WASH WITH SOAP AND WATER PROMPTLY. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR. IF BREATHING IS HARD, GIVE OXYGEN. CALL DOCT OR. INGESTION: DO NOT INDUCE VOMITING. GIVE MILK OR USP MINERAL OIL; GO TO EMERGENCY ROOM..

======= Fire Fight

ing Measures ===============
Flash Point Method:TCC Flash Point:NONE Lower Limits:7 Upper Limits:15 Extinguishing Media:WATER, DRY CHEMICAL OR CARBON DIOXIDE. Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS FOR POSIBLE EXPOSURE TO HYDROGEN CHLORIDE & POSSIBLE TRACES OF PHOSGENE. Unusual Fire/Explosion Hazard:VAPORS CAN BE IGNITED UPON CONTACT WITH HIGH ENERGY, SPARK, FLAME, OE HIGH HEAT. DECOMPOSITION CAN PRODUCE H
YDROGEN CHLORIDE OR POSSIBLE TRACES OF PHOSGENE.
========= Accidental Release Measures ==========
Spill Release Procedures:SPILL-WIPE WITH RAGS OR TOWELS. DO NOT POUR DOWN DRAIN. Neutralizing Agent:NONE
=========== Handling and Storage ===========
Handling and Storage Precautions:STORE IN A COOL PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT USE WITH OR ON ALUMINUM PARTS. Other Precautions:READ AND FOLLOW DIRECTIONS ON LABEL. DO NOT REU SE
CONTAINER. FOR COMMERCIAL/INDUSTRIAL USE ONLY. KEEP FROM REACH OF CHILDREN.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IN HIGH VAPOR AREA, USE RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. Ventilation:LOCAL EXHAUST: ONLY TO REMAIN BELOW 50% OF TLV. Protective Gloves:NITRILE NBR GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment:APRON TO PREVENT ABSORPTION ON TO CLOTHING. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDL ING AND BEFORE EATING OR DRINKING. Supplemental Safety and Health NONE
======================================
HCC:T4 Boiling Pt:B.P. Text:154F/68C Vapor Pres:120 MMHG Vapor Density:4.54 Spec Gravity:1.31 Evaporation Rate & Description Ra
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YE

S

CAUSTICS, OXIDIZERS & ALUMINUM.

Stability Condition to Avoid:OPEN FLAME, HOT GLOWING SURFACES, OR ELECTRIC ARCS.

Hazardous Decomposition Products:HYDROGEN CHLORIDE & POSSIBLE TRACES OF PHOSGENE.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.