

TRUETECH INC -- AMPOULE ASSEMBLY, PYRIDINE (COMPONENT OF M2 -- 6665-01-133-4964

=====  
Product Identification  
=====

Product ID:AMPOULE ASSEMBLY, PYRIDINE (COMPONENT OF M2

MSDS Date:02/01/1992

FSC:6665

NIIN:01-133-4964

Kit Part:Y

MSDS Number: BRLZT

=== Responsible Party ===

Company Name:TRUETECH INC

Address:680 ELTON AVE

City:RIVERHEAD

State:NY

ZIP:11901-2555

Country:US

Info Phone Num:516-727-8600

Emergency Phone Num:516-727-8600

CAGE:06421

=== Contractor Identification ===

Company Name:TRUETECH INC

Address:680 ELTON AVE

Box:City:RIVERHEAD

State:NY

ZIP:11901-2555

Country:US

Phone:516-727-8600

CAGE:06421

=====  
Composition/Information on Ingredients  
=====

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III)

CAS:109-86-4

RTECS #:KL5775000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 25 PPM

ACGIH TLV:S, 5 PPM; 9293

Ingred Name:4-BENZYL PYRIDINE

CAS:2116-65-6

RTECS #:US2625000

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CORROSIVE MATERIAL. IRRITATING TO SKIN, EYES, MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT. INHALATION OF HIGH CONCENTRATIONS MAY ALSO PRODUCE HEADACHE, NAUSEA, DIZZINESS AND VOMITTING

G. SWALLOWING MAY CAUSE ABDOMINAL PAIN, DIZZINESS,CENTRAL NERVOUS SYSTEM DEPRESSION, KIDNEY DAMAGE, LIVER DAMAGE.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:IRRITATION OF EYES, SKIN OR MUCOUS MEMBRANE. HEADACHE, DIZZINESS, NAUSEA, ABDOMINAL DISCOMFORT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:FLUSH SKIN OR EYES THOROUGHLY WITH WATER.

FOR INHALATION,

REMOVE TO FRESH AIR. FOR SWALLOWING, INDUCE VOMITTING, DRINK MILK OR EGG WHITE. CALL PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:115F,46C

Lower Limits:2.5

Upper Limits:14

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL-TYPE OR UNIVERSAL TYPE FOAMS.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:EMITS TOXIC FUMES OF NITROGEN OXIDES

=

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT. COLLECT FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES.

AVOID BREATHING OF VAPORS. USE WITH ADEQUATE VENTILATION. KEEP FROM FREEZING.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Expos

ure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:MECHANICAL (GENERAL)

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYEBATH AND SAFETY SHOWER

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

KEY 1:F6. THIS ITEM IS PART OF A KIT. SEE THIS NSN AND CAGE FOR INFORMATION ON OTHER COMPONENTS OF THIS KIT.

===== Physical/Chemical Properties =====

=====

HCC:F2

Boiling Pt:B.P. Text:256F,125C

Melt/Freeze Pt:M.P/F.P Text:-124F,-87C

Vapor Pres:6.2 @ 20C

Vapor Density:2.62

Spec Gravity:0.966

Evaporation Rate & Reference:0.62(N-BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:WATER WHITE LIQUID, MILD, AGREEABLE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALINE MATERIALS, POTASSIUM OR SODIUM METAL.

Stability Condition to Avoid:HIGH TEMPER

ATURES

Hazardous Decomposition Products:HYDROGEN CHLORIDE, COPPER OXIDE OR COPPER CHLORIDE FUMES, CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manne

r whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.