View NSN Online: https://aerobasegroup.kr/nsn/6850-00-357-7926

Product ID:E-59 REMOVER MSDS Date:01/01/1995 FSC:6850 NIIN:00-357-7926 **MSDS Number: BRMFY** === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID ST **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:310-450-1111 Emergency Phone Num:310-450-1111/800-424-9300(CHEMTREC) CA GE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733 Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC; (ALIPHATIC PETROLEUM DISTILLATES) CAS:64742-88-7 Other REC Limits:NONE RECOMMENDED

Routes of E

ntry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:LIQUID IS MINIMALLY IRRITATING TO THE EYES AND SLIGHT IRRITATING TO THE SKIN. VAPORS MAY BE IRRITATING TO THE NOSE, THROAT AND UPPER RESPIRATORY TRACT, AND CAUSE CNS DEPRESSION. Effects of Overexposure: EYES/SKIN: SLIGHT IRRITATION. INHALATION: IRRITATION AND COUGHING, GIDDINESS AND HEADACHE. INGESTION:NAUSEA, VOMITING. Medical Cond Aggravated by Ex posure: PRE-EXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT: WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS PERSIS T. INGESTION: DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY. ==== Flash Point Method:TCC Flash Point:145F,63C Lower Limits:1 Upper Limits:5 Extinguishing Media: USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE DIRECT STREAM OF WATER. Fire Fighting Procedures: DO NOT ENTER CONFINED FIRE SPACE W/O FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: CONTAINERS EXPO TO INTENSE HEAT FRM FIRE SHOULD BE COOLED W/WATER TO PREVENT VAP PRESSURE BUILD-UP WHICH COULD RUPTURE CONTAINER. 

Spill Release Procedures: ELIMINATE IGNITION SOURCES. WEAR APPROPRIATE PROTECTIVE PROTECTIVE CLOTHING & RESPIRATOR. DIKE & TRANSFER LIQ TO A SALVAGE TANK. SOAK UP RESIDUE WITH ABSORBENT CLAY, SAND OR OTHR MATL.PLACE RAGS & ABSORB ED MATERL IN COVERED CONTAINERS FOR DISPOSAL.

 Handling and Storage Precautions: KEEP AWAY FROM HEAT/IGNITION SOURCES.
STORE IN DRY,COOL,& VENTILATED LOCATION.DO NOT STORE NEAR OXIDIZING MATERIAL. AVOID PHYSICAL DAMAGE TO CANS.
Other Precautions: MINIMIZE CONTACT. USE IN WELL VENTILATED AREA.

Respiratory Protection: IF EXPOSURE EXCEEDS TLV, USE NIOSH APPRVD RESPIRATOR TO PREVENT OVEREXPOSURE. Ventilation: PER MANUFACTURER, PROVIDE LOCAL EXHAUST, OR MECHANICAL

(GENERAL) VENTILATION TO MAINTAIN TLV. Protective Gloves:CHEMICAL RESISTANT. Eye Protection:GOGGLES. Other Protective Equipment:EYE WASH FOUNTAINS AND SAFETY SHOWERS. Work Hygienic Practices:WASH WITH SOAP AND WATER BEFORE EATING,DRINKING, SMOKING OR USING TIOLET FACILITIES. Supplemental Safety and Health

HCC:V4 Boiling Pt:B.P. Text:355F,179C Vapor Pres: