

DOW CORNING CORP -- VALVE LUB. AND SEALANT,DC 111 -- 6850-00-294-0860

=====  
Product Identification  
=====

Product ID:VALVE LUB. AND SEALANT,DC 111

MSDS Date:04/23/1990

FSC:6850

NIIN:00-294-0860

MSDS Number: BRPDD

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:

517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SILICA GEL/SILICA, AMORPHOUS

CAS:11

2945-52-5  
RTECS #:VV7310000  
Fraction by Wt: 9%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:6 MG/M3  
ACGIH TLV:10 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE- DIRECT EYE CONTACT MAY CAUSE  
TEMPORARY DISCOMFORT. A SINGLE LONG SKIN EXPOSURE (24 TO 48 HOURS)  
CAUSES NO KNOWN ADVERSE EFFECTS. NO INJURY IS LIKELY FROM

RELATIVELY SHORT EXPOSURE OF LESS THAN 8 HOURS BY INHALATION.  
SWALLOWING LARGEAMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT. CHRONIC- NO  
KNOWN ADVERSE HEALTH EFFECTS

Effects of Overexposure:EYE REDNESS AND DRYNESS SIMILAR TO WINDBURN,  
DIGESTIVE DISCOMFORT

Medical Cond Aggravated by Exposure:NOT KNOWN

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:WIPE OFF AND  
FLUSH WITH WATER. EYE:FLUSH IMMEDIATELY WITH W  
ATER.

INHALED/INGESTED:NO FIRST AID SHOULD BE NEEDED.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:>212F,>100C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, FOAM OR DRY CHEMICAL.  
WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND  
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL  
FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/

Explosion Hazard:NOT KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP BULK MATERIAL AND PLACE IN LABELED  
PLASTIC OR METAL CONTAINER. USE ABSORBENT MATERIAL TO TAKE CARE OF  
ANY OIL-LIKE RESIDUES.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. AVOID  
CONTACT WITH OXIDIZERS. KEEP CONTAINER CLOSED.

Other Precautions:

WASH THOROUGHLY AFTER HANDLING MATERIAL. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED DURING NORMAL USE OF THIS PRODUCT.

Ventilation:MECHANICAL (GENERAL) RECOMMENDED

Protective Gloves:LATEX RECOMMENDED

Eye Protection:PROTECTIVE GOGGLES/SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION, EMERGENCY SHOWER

Work Hygienic Practices:OBSERVE NORMAL CARE FOR WORKING WITH CHEMICALS.

Supplemental Safet

y and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME NSN.

===== Physical/Chemical Properties =====

HCC:V7

Vapor Pres: