

MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED -- UNKNOWN GASKET --
5330-00-385-7736

===== Product Identification =====

Product ID:UNKNOWN GASKET

MSDS Date:05/18/1993

FSC:5330

NIIN:00-385-7736

MSDS Number: BRPDJ

=== Responsible Party ===

Company Name:MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED

Box:3990

City:COLUMBUS

State:OH

ZIP:43216-5000

Country:US

Info Phone Num:614-238-3131

Preparer's N

ame:DGSC-SSH

CAGE:JO772

=== Contractor Identification ===

Company Name:DEFENSE CONSTRUCTION SUPPLY CENTER

Address:NONE

Box:3990

City:COLUMBUS

State:OH

ZIP:43215-5000

Country:US

Phone:614-238-3131

CAGE:16236

Company Name:MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED

Address:700 ROBBINS AVENUE

Box:3990

City:PHILADELPHIA

State:PA

ZIP:19111-5096

Country:US

Phone:215-697-2000

CAGE:JO772

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12

001-29-5
RTECS #:CI6478500
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:2 FIBERS/CC; A1;9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &
MESOTHEL
IOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER
OF THE BOWEL.
Explanation of Carcinogenicity:CONTAINS A [1332-21-4] WHICH IS
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.
Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.
DIARRHEA, V
OMITING, AND NA USEA.
Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERCULOSIS
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE
THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.
INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCT
OR.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE
Extinguishing Media:NONFLAMMABLE. USE WATER FOG, CARBON DIOXIDE, FOAM,
OR DRY CHEMICAL AS REQUIRED FOR SURROUNDING FIRE.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Rel

ease Measures =====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE- ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP UP CONTAMINATION.

===== Handling and Storage =====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING ITEM. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

M

SDS GENERATED BY HMIS TECHNICIAN. ITEM ASSUMED TO CONTAIN ASBESTOS BASED ON AVAILABLE INFORMATION.

===== Physical/Chemical Properties =====

HCC:T6

Solubility in Water:INSOLUBLE

Appearance and Odor:DRY, MOLDED

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:ACCUMULATIONS OF DUST

ST
Hazardous Decomposition Products:ASBESTOS DUST

===== Disposal Considerations =====

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.
PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS
INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN
APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING
LABEL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.