View NSN Online: https://aerobasegroup.kr/nsn/5330-00-400-6582

MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED -- 12536512 GASKET

5330-00-400-6582

Product ID:12536512 GASKET

MSDS Date:05/20/1993

FSC:5330

NIIN:00-400-6582

MSDS Number: BRPDL === Responsible Party ===

Company Name: MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED

Box:3990

City: COLUMBUS

State:OH

ZIP:43216-5000

Country:US

Info Phone Num:614-238-3131

Preparer's

Name: DGSC-SSH

CAGE:JO772

=== Contractor Identification ===

Company Name: DEFENSE CONSTRUCTION SUPPLY CENTER

Address:NONE

Box:3990

City:COLUMBUS

State:OH

ZIP:43215-5000

Country:US

Phone:614-238-3131

CAGE:16236

Company Name: MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED

Address:700 ROBBINS AVENUE

Box:3990

City:PHILADELPHIA

State:PA

ZIP:19111-5096

Country:US

Phone:215-697-2000

CAGE:JO772

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS, CHRYSOTILE

CAS:

12001-29-5
RTECS #:CI6478500
Other REC Limits: NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TI V·2 FIBERS/CC: A1·9293

========== Hazards Identification ================

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION. INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, & MESOTH

- ELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER OF THE BOWEL.
- Explanation of Carcinogenicity: CONTAINS A [1332-21-4] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.
- Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES: IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS. DIARRHEA,

VOMITING, AND NA USEA.

Medical Cond Aggravated by Exposure: ASTHMA, EMPHYSEMA, AND TUBERCULOSIS ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR. INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

========= Fire Fighting Measures ===============

Flash Point:NONFLAMMABLE

Extinguishing Media:NONFLAMMABLE. USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL AS REQUIRED FOR SURROUNDING FIRE.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

====== Accidental R

مممما	ana Manauran	
	NADSCHIEDC	

Spill Release Procedures: VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE- ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTA NT AND THEN SHOVEL OR MOP UP CONTAMINATION.

============ Handling and Storage ================

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. U

SED ITEMS SHALL BE WETTED

BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDE RAL REGULATIONS.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APP

ARATUS IF REQUIRED FOR

HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves: COTTON OR LEATHER

Eye Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING ITEM. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. ITEM ASSUMED TO CONTAIN ASBESTOS BASED ON AVAILABLE INFORMATION.

======== Physical/Chemical Properties ============

HCC:T6 Solubility in Water:INSOLUBLE Appearance and Odor:DRY, MOLDED Percent Volatiles by Volume:0

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS Stability Condition to Avoid:ACCUMULATIONS OF

## DUST

Hazardous Decomposition Products: ASBESTOS DUST

======= Disposal Considerations ==========

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.
PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS
INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN
APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING
LABEL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.