View NSN Online: https://aerobasegroup.kr/nsn/5970-01-185-3375

## CONAP INC. -- CONATHANE CE-1164 ( ASTRAUTICS P/N14554-001 -- 5970-01-185-3375

======== Product Identification ============

Product ID:CONATHANE CE-1164 (ASTRAUTICS P/N14554-001

MSDS Date:07/21/1989

FSC:5970

NIIN:01-185-3375

MSDS Number: BRPHC
=== Responsible Party ===
Company Name: CONAP INC.
Address: 1405 BUFFALO STREET

City:OLEAN State:NY ZIP:14760 Country:US

Info Phone Num:716-372-9650

**Emergency Phone Num** 

:716-372-9650

Preparer's Name: GEORGE C. KARPIN

CAGE:16245

=== Contractor Identification ===

Company Name: ASTRONAUTICS CORP OF AMERICA, 414-447-8200

Address:4115 N TEUTONIA AVE

Box:523

City:MILWAUKEE

State:WI ZIP:53201 Country:US

Phone:414-447-8200

CAGE:10138

Company Name: CONAP INC., WHOLLY OWNED SUBSIDIARY OF CYTEC INDUSTRIES

INC.

Address:1405 BUFFALO STREET

Box:City:OLEAN

State:NY ZIP:14760 Country:US

Phone:716-372-9650

CAGE:16245

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 10-20%

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: PROPYLENE GLYCOL METHYL ETHER ACETATE

CAS:108-65-6

RTECS #:Al8295000 Fraction by Wt: 20-30% Other REC Limits:100 PPM

Ingred Name:TOLUENE-2,4-DIISOCYANATE (TDI) (SARA III)

CAS:584-84-9

RTECS #:CZ6300000

Fraction by Wt: 25GM SOLID RESIN/KG Routes of Entry: Inhalation:YES Sk

in:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:LIQUID IS SEVERELY IRRITATING TO BODY
TISSUES. TOLUENE DIISOCYANATE MAY SENSITIZE SEVERE ALLERGIC
REACTIONS SUCH AS CHEMICAL ASTHMA. PEL FOR TDI IS BELOW THE ODOR
THRESHOLD. SOLVENTS ARE ABSORBED THRO UGH SKIN. CHRONIC BREATHING
OVEREXPOSUREMAY CAUSE PERMANENT CENTRAL NERVOUS SYSTEM DAMAGE KNOWN
AS PAINTERS SYNDROME.

Explanation of Carcinogenicity: TOLUENE DIISOCYANA

TE IS LISTED BY NTP

AND IARC.SEE INDIVIDUAL REPORTS FOR DETAILS.

Effects of Overexposure: EYE: SEVERE IRRITATION. SKIN: CAUSES

IRRITATION, DEFATTING, DERMATITIS, & SENSITIZATION. INHALATION:


CAUSES RESPIRATORY IRRITATION, FLU-LIKE SYMPTOMS. ALLERGIC RESP

REACTION MAY OCCUR IN SENSITIZED PERSONS .CAUSES

DIZZ, WEAKNESS, FATIGUE, NARCOSIS, LOSS OF APPETITE, ETC.. INGESTION: G/I

IRRITATION, HEADACHE, NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:PEOPLE SENSITIZED TO TOLUENE



Handling and Storage Precautions:STORE IN TIGHTLY CLOSED IN DRY AREA.STORE BETWEEN 32-122F (50-81F,IDEAL).PROTECT FROM MOISTURE. PRODUCT WILL POLYMERIZE SLOWLY AT HIGHER TEMPERATURE.

Other Precautions:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. TREAT THEM WITH T

HE RESPECT DUE FULL ONES. DO NOT CUT, WELD, ETC.. ON THEM. AVOID SPARKS AND OPEN FLAMES. STORE IN COOL PLACE BECAUSE CLOSED CONTAINERS M AY EXPLODE IN HEAT.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:USE POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR ANY TIME THE EXPOSURE IS ABOVE THE CEILING, SHORT TERM EXPOSURE LEVEL,OR PEL, AND AT AL TIMES DURING SPRAYING OPERATIONS. OTHER RESPIRATORS MAY BE USED FO R SHORT (1 HOUR) EXPOSURES ONLY

Ventilation:GENERAL VENTILATION SUPPLEMENTED WITH LOCAL EXHAUST, AS NEEDED T MAINTAIN EXPOSURES BELOW PEL/TLV.

Protective Gloves: NEOPREVE RUBBER

Eye Protection: GOGGLES OR FACE SHIELD NO CONTACTS!!

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. COVER AS MUCH SKIN AS POSSIBLE DURING OPERATIONS.

Work Hygienic Practices: USE STRICT CHEMICAL HYGIENE PRACTICES. AVOID ALL CONTACT POSSIBLE. WASH THOROUGHLY AFTER USING.

Supplemental Safety and Health

TDI LD50 = 5800MG/KG; TDI

LC50 = 4 HR @ 16-50PPM. INHALATION AND SKIN

ARE MOST DAMAGING EXPOSURES. ALTERNATE DECONTAMINANT: SOLUTION OF UNION CARBIDE'S TERGITOL TMN-10 (20%) AND WATER(80%). \*\*\*NOTE: ON 20SEP93, ASTRONAUTICS INFORMED HMIS THAT THEY SUPPLIED CONAP CE-1164 FOR THIS NSN, BUT HAD NO MSDS. HMIS OBTAINED IT.

======== Physical/Chemical Properties ==========

HCC:F2

NRC/State Lic Num:NONE

Vapor Pres:3.7/8 MM Vapor Density:3.7

Spec Gravity:1.05

Solubility in Water: REACTS WIT

H WATER

Appearance and Odor:CLEAR YELLOW VISCOUS LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:40

======== Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, WATER, ALCOHOLS, AMINES, STRONG BASES, METAL COMPOUNDS, SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid:HIGH STORAGE TEMPERATURES, IGNITION SOURCES

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, TRACES ON HYDROGEN CYANIDE, O

## XIDES OF NITROGEN, TOLUENE DIISOCYANATE.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL,STATE,LOCAL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE DUE TO PRODUCT RESIDUE AND FLAMMABLE SOLVENT VAPOR.DECONTAMINATE CONTAINERS PRIOR TO DISPOSAL.DO NOT HEAT O R CUT EMPTY CONTAINERS WITH ELECTRIC ORGAS TORCH.

Disclaimer (provided with this information by the compiling agencies): This information is f ormulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.