

UOP INC -- UNICOR, TYPE J, CORROSION INHIBITOR -- 6850-00-292-9780  
===== Product Identification =====

Product ID:UNICOR, TYPE J, CORROSION INHIBITOR

MSDS Date:01/01/1991

FSC:6850

NIIN:00-292-9780

MSDS Number: BRQNS

=== Responsible Party ===

Company Name:UOP INC

Address:25 E ALGONQUIN RD

City:DES PLAINES

State:IL

ZIP:60017-5017

Country:US

Info Phone Num:708-391-2123

Emergency Phone Num:708-391-212

3/800-424-9300(CHEMTREC)

CAGE:02QC3

=== Contractor Identification ===

Company Name:UOP LLC

Address:25 E ALGONQUIN RD

Box:City:DES PLAINES

State:IL

ZIP:60017-5017

Country:US

Phone:847-391-3189 FAX: 847-391-2953

CAGE:02QC3

===== Composition/Information on Ingredients =====

Ingred Name:UNSATURATED DIMER FATTY ACID

CAS:61788-89-4

Fraction by Wt: 40-70%

Other REC Limits:NONE ESTABLISHED

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:HEAVY AROMATIC NAPHTHA

CAS:64

742-94-5

RTECS #:WF3100000

Fraction by Wt: 40-70%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION-REPEATED OR PROLONGED

INHALATION OF SOLVENT VAPORS MAY CAUSE IRRITATION OF THE  
RESPIRATORY TRACT. EYE-AROMATIC SOLVENTS ARE KNOWN EYE IRRITANTS.  
DERMAL-SOLVENTS ARE KNOWN TO REMOV

E THE NATU RAL OILS FROM THE  
SKIN.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:INHALATION-INHALATION OF HIGH SOLVENT VAPOR  
CONCENTRATIONS MAY CAUSE DIZZINESS, HEADACHES, RESPIRATORY PROBLEMS  
OR CENTRAL NERVOUS SYSTEM DEPRESSION. DERMAL-REPEATED OR PROLONGED  
CONTACT MAY RESULT IN DERMATITIS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:SKIN: APLY A

GENEROUS AMOUNT OF WATERLESS HAND CLEANER TO THE  
AFFECTED AREA. RUB BRISKLY ONTO THE SKIN, ON AND AROUND THE  
AFFECTED AREA. REMOVE THE MIXTURE OF CLEANER-ADDITIVE WITH PAPER  
TOWELS OR CLE AN, DRY RAGS; EYE: FLUSH WITH LARGE AMOUNTS OF WATER  
FOR 15 MINUTES; INHALE: REMOVE TO FRESH AIR & GET MEDICAL  
ATTENTION; INGEST: DO NOT INDUCE VOMITING. GET MEDICAL ASSISTANCE.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>149F,>

65C

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:MAY PRODUCE IRRITATING OR POISONOUS  
GASES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ISOLATE THE AFFECTED AREAS AND KEEP OUT ALL  
UNAUTHORIZED PERSONNEL. CONFINE ENTRY TO THE CONTAMINATED AREA TO  
THOSE PERSONS WHO ARE PROPERLY PROTECTED. REMOVE SOURCES OF  
IGNITON. CLEAN UP CONTAMINATE



=====

Stability Indicator/Materials to Avoid: YES

REACTIVE WITH MINERAL ACIDS AND BASES.

Stability Condition to Avoid: THERMAL DECOMPOSITION, INCOMPATIBLE MATERIALS.

Hazardous Decomposition Products: CARBON MONOXIDE, OXIDES OF NITROGEN AND OTHER IRRITATING OR POISONOUS GASES.

===== Disposal Considerations =====

Waste Disposal Methods: WASTE MATERIAL, INCLUDING CONCENTRATED LIQUIDS, CONTAMINATED ABSORBENT AND MATERIALS FROM SPILL CLEAN-UP PROCEDURE

S, MUST BE HANDLED IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume re

sponsibility for the suitability of this information to their particular situation.