

KAPP ALLOY AND WIRE INC -- TIN-LEAD ALLOY CORE SOLDER -- 3439-00-819-5533

=====
Product Identification
=====

Product ID:TIN-LEAD ALLOY CORE SOLDER

MSDS Date:08/01/1993

FSC:3439

NIIN:00-819-5533

MSDS Number: BRSTV

=== Responsible Party ===

Company Name:KAPP ALLOY AND WIRE INC

Address:ONE KLEIN ST

Box:1188

City:OIL CITY

State:PA

ZIP:16301

Country:US

Info Phone Num:814-676-0613

Emergency Phone Num:81

4-676-0613

CAGE:44851

=== Contractor Identification ===

Company Name:COORDINATED WESTERN INC

Address:2968 TEAGARDEN ST

Box:City:SAN LEANDRO

State:CA

ZIP:94977

Country:US

Phone:510-895-8585

CAGE:0U0J2

Company Name:KAPP ALLOY AND WIRE INC

Address:1 KLEIN ST

Box:City:OIL CITY

State:PA

ZIP:16301

Country:US

Phone:814-676-0613

CAGE:44851

=====
Composition/Information on Ingredients
=====

Ingred Name:TIN (SN)

CAS:7440-31-5

RTECS #:XP7320000

Other REC Limits:NONE RECOMMENDED

OSHA PEL

:2 MG/M3
ACGIH TLV:2 MG/M3; 9293

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:AZELAIC ACID
CAS:123-99-9
RTECS #:CM1980000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:UREA
CAS:57-13-6
RTECS #:YR6250000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHE
D.

Ingred Name:ETHYLENEDIAMINE DIHYDROCHLORIDE
CAS:333-18-6
RTECS #:KV3850000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:ETHYLAMINE HYDROCHLORIDE
CAS:557-66-4
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:SUCCINIMIDE
CAS:123-56-8
RTECS #:WN2200000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

=====
===== Hazards Identification =====

=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE- UNLIKELY. CHRONIC- HIGH LEVELS OF AIRBORNE OR INGESTED LEAD MAY RESULT IN ANEMIA, INSOMNIA, WEAKNESS, CONSTIPATION, KIDNEY, NERVOUS SYSTEM AND REPRODUCTIVE EFFECTS. EXPOSURE TO LEAD MAY RESULT IN INJURY TO A DEVELOPING FETUS.

Explanation of Carcinogenicity:CONTAINS LEAD
Effects of Overexposure:EYE IRRITATION, ABDOMINAL PAIN, WEAKNESS, CONSTIPATION, NAUSEA

Medical Cond Aggravated by Exposure:DISEASES OF THE BLOOD AND BLOOD FORMING ORGANS, KIDNEYS, NERVOUS SYSTEM AND POSSIBLY REPRODUCTIVE SYSTEMS MAY BE AGGRAVATED BY OVEREXPOSURE TO LEAD.

===== First Aid Measures =====

First Aid:CALL A DOCTOR IF SYMPTOMS PERSIST. EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED.
ORAL:IF CONSCIOUS, INDUCE VOMITING. CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. NOTE:OCCASIONAL BLOOD TESTING FOR LEAD LEVEL SHOULD BE ROUTINE FOR INDIVIDUALS WHO ARE CHRONICALLY EXPOSED TO LEAD.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:WATER FOG, FOAM, CARBON DIOXIDE. DO NOT USE WATER ON FIRE WHERE MOLTEN METALS IS PRESENT.
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:MOLTEN METALS PRODUCE FUME OR VAPOR THAT IS TOXIC. REACTS VIOLENTLY WITH OXIDIZING AGENTS.

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT AND USE. IF CONTAMINATED OR IN SMALL PARTICLES, VACUUM OR COLLECT MATERIAL. NEVER USE ANY METHOD WHICH GENERATE DUST. DO NOT USE FORCED AIR F

OR CLEANING. WEAR

NIOSH-APPROVED DUST MASK IF DUSTY CONDITION.

Neutralizing Agent:NOT RELEVANT

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM INCOMPATIBLE MATERIALS.
AVOID ACCIDENTAL INGESTION. FOOD AND DRINK SHOULD NOT BE CONSUMED
IN AREAS WHERE METAL EXPOSURES ARE POSSIBLE.

Other Precautions:READ WARNING LABELS. KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL USE ONLY. DO NOT GENERATE DUST. DO NOT BREATHE DUS

T
OR FUMES. AVOID CONTACT WITH DUST OR FUMES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:REQUIRED IF TLV'S ARE NOT BEING MAINTAINED. USE
NIOSH APPROVED RESPIRATOR FOR LEAD DUST/FUME (HIGH EFFICIENCY
FILTERS) IF TLVS ARE EXCEEDED.

Ventilation:LOCAL DUST PICK UP AND ADEQUATE VENTILATION

Protective Gloves:HEAT RESISTANT DURING SOLDERING

Eye Protection:FACE SHIELD/GOGGLES DURING SOLDERING

Other Protective Equipment:INSTALL EYE WASH STATIO

N.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:3191F (PB)

Spec Gravity:8.9 (60SN/40PB)

Evaporation Rate & Reference:NOT RELEVANT

Solubility in Water:INSOLUBLE

Appearance and Odor:SILVERY, METALLIC - NO ODOR

=====
===== St

ability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS (E.G. CHLORINE TRIFLUORIDE, HYDROGEN PEROXIDE),
SODIUM AZIDE, AMMONIA & ACETYLENE

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: LEAD OXIDE FUME AND OR LEAD PARTICULATE
MAY BE EVOLVED.

===== Disposal Considerations =====

Waste Disposal Methods: NEVER DISPOSE OF IN TRASH. HOLD FOR RECYCLING OR
DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the
suitability of this information to their
particular situation.