View NSN Online: https://aerobasegroup.kr/nsn/6850-00-181-7933 HI-PORT SERVICES; DIVISION OF HI-PORT INDUSTRIES -- ANTIFREEZE, ETHYLENE GLYCOL, INHIBITED, HD -- 6850-00-181-7933 Product ID:ANTIFREEZE, ETHYLENE GLYCOL, INHIBITED, HD MSDS Date:07/01/1991 FSC:6850 NIIN:00-181-7933 MSDS Number: BRTDW === Responsible Party === Company Name: HI-PORT SERVICES; DIVISION OF HI-PORT INDUSTRIES Address:409 E. WALLISVILLE ROAD City:HIGHL ANDS State:TX ZIP:77562 Info Phone Num:713-426-3541 Emergency Phone Num:713-426-3541(CHEMTREC 800-424-9300) Preparer's Name: MICHAEL T. BUSCHEK CAGE: JO790 === Contractor Identification === Company Name: HI-PORT INDUSTRIES INC Address:409 E. WALLISVILLE ROAD Box:755 **City:HIGHLANDS** State:TX ZIP:77562-3827 Country:US Phone:713-426-3541(CHEMTREC 800-424-9300) **CAGE:9N129** Company Name: HI-PORT SERVICES, DIVISION OF HI-PORT INDUSTRIES Address:409 E WALLISVILLE ROAD City:HIGHLANDS State:TX ZIP:77562 Phone:7 13-426-3541 CAGE:JO790 Company Name: OLD WORLD AUTOMOTIVE PRODUCTS INC

Address:4065 COMMERCIAL AVE

Box:City:NORTHBROOK State:IL ZIP:60062 Country:US Phone:708-559-2000 CAGE:0FGA3 Company Name: VALDES G ENTERPRISES INC Address:627 S VERMONT Box:City:PALATINE State:IL ZIP:60067-6949 Country:US CAGE:3J032

Ingred Name: ETHYLENE GLYCOL (SARA III)

OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL CAS:111-46-6 RTECS #:ID5950000 Fraction by Wt: 0-5% Other REC Limits:25 PPM TLV

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PRIMARY IRRITATION TO SKIN, PRIMARY IRR ITATION TO EYES, CAN BE ABSORBED THROUGH THE SKIN, MAY CAUSE ABDOMINAL IRRITATION. Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA. Effects of Overexposure:SKIN IRRITATION, DEFATTING, DERMATITIS, EYE

IRRITATION, REDNESS, TEARING, BLURRED VISION, HARMFUL OR FATAL IF SWALLOWED, NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

======= First Aid Me

First Aid:SKIN: FLUSH WITH PLENTY OF WATER. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES AND GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF BREATHING DIFFICULT, GIVE OXYGEN. IF BREATHING STOPPED, GIVE ARTIFICIAL RESPIRATION. INGESTION: CALL PHYSICIAN IMMEDIATELY! INDUCE VOMITING PROMPTLY FOLLOWING PHYSICIANS INSTRUCTIONS OR BY STICKING FINGER DOWN THROAT.

FΙ

ash Point Method:TCC Flash Point:244F,118C Lower Limits:1.5% Upper Limits:NOT GIVEN Extinguishing Media:NFPA CLASS B EXTINGUISHERS, DRY CHEMICAL, FOAM, CARBON DIOXIDE Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE ON FIRE BUT CAN PROTECT FIRE FIGHTERS AND COOL CLOSED CONTAINERS. USE FOG NOZZLES IF WATER IS USED. USE PROPER PROTECTIVE EQUIPMT Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT. APPLYING TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. EMPTY CONTAINER VERY HAZARDOUS. Spill Release Procedures: MOP UP WITH ABSORBENT MATERIAL AND TRANFER TO HOOD. ISOLATE FROM OXIDIZERS AND OPEN FLAME. PROPER PERSONAL PROTECTION SHOULD BE USED IN SPILL AREA. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: AVOID FREE FALL OF LIQUID. GROUND CONTAINER S WHEN TRANSFERRING. Other Precautions: DO NOT CUT, BRAZE OR WELD. EMPTY CONTAINER VERY HAZARDOUS. Respiratory Protection: USE A NIOSH APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS IF CONCENTRATIONS ABOVE TLV. Ventilation:LOCAL EXHAUST NECESSARY. VENTILATE TO KEEP AIR CONCENTRATIONS BELOW 45 PPM. Protective Gloves: IMPERVIOUS Eye Protection: GOGGLES OR FACE SHIELD Other Protective Equipment: IMPERVIOUS A PRON AND FOOTWEAR Work Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING. Supplemental Safety and Health WASH CLOTHING BEFORE REUSE. HCC:V5 Boiling Pt:B.P. Text:340F,171C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:0.4 Vapor Density:2.1 Spec Gravity:1.12 pH:9-11.5 Evaporation Rate & amp; Reference:NOT GIVEN Solubility in Water:NOT GIVEN Appearance and Odor: GREEN L

Stability Indicator/Materials to Avoid:YES

ISOLATE FROM STRONG OXIDIZING AGENTS SUCH AS PERMANGANTES, CHROMATES AND PEROXIDES.

Stability Condition to Avoid:ISOLATE FROM HEAT AND OPEN FLAME Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE FROM

BURNING

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

accument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.