

BREN-TRONICS -- NICKEL-CADMIUM BATTERY, SEALED BB-557/U -- 6140-01-071-5070

===== Product Identification =====

Product ID:NICKEL-CADMIUM BATTERY, SEALED BB-557/U

MSDS Date:08/05/1993

FSC:6140

NIIN:01-071-5070

MSDS Number: BRZYY

=== Responsible Party ===

Company Name:BREN-TRONICS

Address:10 BRAYTON COURT

City:COMMACK

State:NY

ZIP:11725

Country:US

Info Phone Num:(516)-499-5155

Emergency Phone Num:(5

16)-499-5155

Preparer's Name:CECOM SAFETY OFFICE

CAGE:DO086

=== Contractor Identification ===

Company Name:BREN-TRONICS

Address:10 BRAYTON CT

Box:City:COMMACK

State:NY

ZIP:11725-5504

Phone:516-499-5155

CAGE:DO086

Company Name:BREN-TRONICS INC

Address:10 BRAYTON CT

Box:City:COMMACK

State:NY

ZIP:11725-3104

Country:US

Phone:631-499-5155

CAGE:51828

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM (SARA III)

CADMIUM & CADMIUM HYDROXIDE 11-2

6%  
CAS:7440-43-9  
RTECS #:EU9800000  
Fraction by Wt: 11-26%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:SEE 1910.1027  
ACGIH TLV:0.01 MG/M3 DUST;9394  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM HYDROXIDE  
CADMIUM & CADMIUM HYDROXIDE 11-26%  
CAS:21041-95-2  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.1 MG/M3 (CD FUME)  
ACGIH TLV:0.05 MG/M3 (CD FUME)

Ingred Name:COBALT (SARA III)  
COBALT & COBALT HYDROXIDE (TRACE AMOUNTS)  
CAS:7440-48-4  
RTECS #:GF8750000

Fraction by Wt: TRACE  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.1 MG/M3;AS CO  
ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:COBALT HYDROXIDE  
COBALT & COBALT HYDROXIDE (TRACE AMOUNTS)  
CAS:21041-93-0  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NICKEL (SARA III)  
NICKEL AND NICKEL HYDROXIDE 13-29%  
CAS:7440-02-0  
RTECS #:QR5950000  
Fraction by Wt: 13-29%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3; 9293

Ingred Name:NICKEL HYDROXIDE (S

ARA III)  
NICKEL & NICKEL HYDROXIDE 13-29%  
CAS:12054-48-7  
RTECS #:QR7040000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG NI/M3  
ACGIH TLV:0.1 MG NI/M3; 9293  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE (SARA III)  
CAS:1310-58-3  
RTECS #:TT2100000  
Fraction by Wt: < 3%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:C, 2 MG/M3  
ACGIH TLV:C 2 MG/M3; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====  
=

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:INTACT BATTERIES PRESENT NO SPECIFIC  
HAZARDS. BURNING BATTERIES MAY EMIT TOXIC FUMES. LEAKING  
BATTERIES LEAK CORROSIVE MATERIAL IRRITATING TO SKIN, EYES AND  
MUCOUS MEMBRANES  
Explanation of Carcinogenicity:CD, NI, ARE NTP SUSPECT CARCINOGENS. CD  
IS IARC CARCINOGEN.  
Effects of Overex  
posure:ELECTROLYTE EXPOSURE TO SKIN/EYES WILL CAUSE  
SEVERE IRRITATION. INHALATION OF FUMES MAY CAUSE SEVERE  
RESPIRATORY IRRITATION.  
Medical Cond Aggravated by Exposure:RESPIRATORY ALIMENTS- W/BURNING  
BATTERIES SKIN CONDITIONS- W/ LEAKING BATTERIES

===== First Aid Measures =====

First Aid:IF BATTERY CONTENTS COME IN CONTACT WITH THE BODY WASH  
AFFECTED AREA FOR AT LEAST 15 MINUTES WITH CLEAN WATER.DO NOT  
ATTEMPT TO NEUTRALIZE. SEEK MEDI

CAL ATTENTION PROMPTLY.

===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE OR DRY CHEMICAL FIRE EXTINGUISHER,  
10-B:C

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE SELF CONTAINED  
BREATHING APPARATUS. BATTERY/CELLS MAY RELEASE TOXIC FUMES, IF  
SUBJECT TO FIRE/EXTREME HEAT.

Unusual Fire/Explosion Hazard:STRONG OXIDERIZERS (E.G.,ACIDS) AND FIRE.

===== Accidental Release Measures =====

Spill Release Pr

ocedures:SPILL OR LEAK PROCEDURES (PRECAUTIONS FOR SAFE  
HANDLING & USE) AVOID SKIN OR EYE CONTACT. USE NON FLAMMABLE  
ABSORBENT MATERIAL FOR CLEAN-UP. COORDINATE WITH INSTALLATION  
SAFETY AND ENVIRONMENTAL OFFIC ES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT ABUSE OR SHORT CIRCUIT. STORE  
COOL, DRY AND IN A WELL VENT AREA. SEPARATE FROM OTHER HAZARDOUS  
MATERIALS.

AREA APPROVED BY LOCAL FIRE DEPARTM

Other Precautions:DO NOT INVERT BATTERY OR CAUSE TO SPILL. RECHARGE  
IAW METHODS SPECIFIED IN APPLICIABLE TECHNICAL MANUAL. DO NOT  
OVERCHARGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF BATTERIES ARE BURNING USE SCBA

Ventilation:CONTACT LOCAL SAFETY/INDUSTRIAL HYGIENE OFFICE TO DETERMINE  
IF LOCAL EXHAUST VENTILATION IS NEEDED

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:CHEMICAL S  
AFETY GLASSES/GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON

Work Hygienic Practices:AVOID SKIN EYE CONTACT WITH ELECTROLYTE. DO NOT  
EAT OR SMOKE IN BATTERY SERVICE AREA.

Supplemental Safety and Health

CONTRACT # DAAB07-91-C-R002 THIS MSDS WAS CODED FROM A CECOM MATERIAL  
SAFETY DATA SHEET NOT THE MANUFACTUERS. CECOM SAFETY OFFICE, FT  
MONMOUTH, NJ 07703-5024 AUTOVON 995-3112.

===== Physical/Chemical Properties =====

pH:UNK

Appearance and

Odor:NICKEL-CADMIUM BATTERY,SEALED

Percent Volatiles by Volume:UNK

Corrosion Rate:UNK

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS (E.G., ACIDS). STORE SEPARATELY FROM OTHER  
HAZARDOUS MATERIALS

Stability Condition to Avoid:FIRE AND EXTREME HEAT. DO NOT SHORT  
CIRCUIT OR OVERCHARGE

Hazardous Decomposition Products:WHEN EXPOSED TO FIRE OR EXTREME HEAT,  
BATTERIES MAY EMIT TOXIC FUMES

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH ALL  
APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. COORDINATE WITH  
SUPPORTING INSTALLATION AND/OR MACOM ENVIRONMENTAL OFFICE PRIOR TO  
DISPOSAL

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or  
implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.