

HF SCIENTIFIC INC. -- CAPTURED FUEL TEST KIT -- 6630-01-248-5389

===== Product Identification =====

Product ID:CAPTURED FUEL TEST KIT

MSDS Date:01/01/1989

FSC:6630

NIIN:01-248-5389

MSDS Number: BSCZZ

=== Responsible Party ===

Company Name:HF SCIENTIFIC INC.

Address:3170 METRO PARKWAY S.E.

City:FORT MYERS

State:FL

ZIP:33916-7539

Country:US

Info Phone Num:813-337-2116/800-424-9300

Emergency Phone Nu

m:813-337-2116 FAX 800-424-7643

CAGE:58177

=== Contractor Identification ===

Company Name:HF SCIENTIFIC INC.

Address:3170 METRO PARKWAY S.E.

City:FORT MYERS

State:FL

ZIP:33916-7539

Country:US

Phone:941-337-2116

CAGE:58177

===== Composition/Information on Ingredients =====

Ingred Name:KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: 50%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DECANE

CAS:124-18-5

RTECS #:HD6550000

Fraction by Wt: 50%

Other REC Limits:NONE RECOMME

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: IRRITATION, DRYING. EYE:
IRRITATION. INHALATION: IRRITATION, CNS DEPRESSION.
INGESTION:IRRITATION OF GI TRACT. ASPIRATION INTO LUNGS MAY CAUSE
CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. CHRONIC:D ERMATITIS.
Explanation of Carcinogenicity:MIDDLE DISTILLATES HAVE CA
USED SKIN
CANCER IN LABORATORY ANIMALS.
Effects of Overexposure:SKIN: IRRITATION, REDNESS, EDEMA, DRYING.
EYE:IRRITATION, REDNESS, TEARING. INHALATION: COUGHING,
DROWSINESS. INGESTION: NAUSEA, VOMITING.
Medical Cond Aggravated by Exposure:PULMONARY AND SKIN DISEASES.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.
EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN
CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS
PERSIS T. INGESTION:DO NOT INDUCE VOMITING, GET MEDICAL HELP
IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>100F,>38C
Lower Limits:0.8%
Upper Limits:5.42%
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM, CO2, HALON.
Fire Fighting Procedures:USE WATER TO KEEP FIRE EXPOSED CONTAINERS
COOL. USE WATER SPRAY TO DISPERSE VAPORS & WEAR SELF-CONTAINED
BREATHING APPARATUS WHEN ATTEMPTING TO STOP LEAK/SPILL.
Unusual Fire/Explosion Hazard:VAPOR-AIR MIXTURE ARE EXPLOSIVE ABOVE
FLASH POINT. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A
CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION.
USE SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR MASK FOR
LARGE SPILLS IN CONFINED AREA. CON

TAINT SPILL IF POSSIBLE. DIKE, AND
VACUUM UP OR ABSORB ON INERT ABSORBENT & SHOVEL UP.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT & FLAME. USE ONLY
IN WELL VENTILATED AREAS. AVOID BREATHING OF MIST/ VAPOR. DON'T
PRESSURIZE.
Other Precautions:KEEP HEAD AWAY FROM CONTAINER WHEN OPENING OR
DISPENSING. AVOID CONTACT.

===== Exposure Controls/Personal Protection =====
===

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN
SPRAYING OR USING IN CONFINED SPACES.
Ventilation:NORMAL
Protective Gloves:CHEMICAL RESISTANT
Eye Protection:GOGGLES, FACE SHIELD
Other Protective Equipment:EYEWASH
Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH
THIS PRODUCT.
Supplemental Safety and Health
MIDDLE DISTILLATES HAVE CAUSED SKIN CANCER & KIDNEY DAMAGE IN
LABORATORY ANIMALS.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:350F,177C
Vapor Pres: 1 MMHG
Vapor Density:4.7
Spec Gravity:0.75
Evaporation Rate & Reference: