

HARRINGTON INC,TONER MFG DIV -- HARRINGTON 9201-TYPE H ELECTROGRAPHIC LIQUID
TONER PREMIX -- 6850-01-173-3992

===== Product Identification =====

Product ID:HARRINGTON 9201-TYPE H ELECTROGRAPHIC LIQUID TONER PREMIX

MSDS Date:12/13/1993

FSC:6850

NIIN:01-173-3992

MSDS Number: BSFSV

=== Responsible Party ===

Company Name:HARRINGTON INC,TONER MFG DIV

Address:38 SAGINAW DR

Box:92490

City:ROCHESTER

State

:NY

ZIP:14692-0490

Country:US

Info Phone Num:716-473-9551

Emergency Phone Num:716-473-9551

CAGE:NO126

=== Contractor Identification ===

Company Name:HARRINGTON INC,TONER MFG DIV

Address:38 SAGINAW DR

Box:92490

City:ROCHESTER

State:NY

ZIP:14692-0490

Country:US

Phone:716-473-9551

CAGE:NO126

Company Name:HARRINGTON TONER MFG TONER MFG DIV

Box:92490

City:ROCHESTER

State:NY

ZIP:14692

Country:US

Phone:716-473-9551

CAGE:5J804

===== Composition/Information on Ingredients =====

Ingred

Name:MINERAL SPIRITS/ISOPARAFFINIC HYDROCARBON SOLVENT
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 90%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:PIGMENT, TRADE SECRET
Other REC Limits:NONE SPECIFIED

Ingred Name:POLYMER,TRADE SECRET
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >10 G/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: NOT AN IRRITANT. SKIN: NON-SENSITIZING. MAY CAUSE IRRITATION AND DERMATITIS WITH PROLONGED CONTACT. INHALATION: INTENTIONAL INHALATION MAY RESULT IN ABNORMAL HEART RHYTHMS, RESPIRATORY ARREST, CNS TOXICITY. INGESTION: POSES MAXIMUM RISK OF SEVERE RESPIRATORY DISTRESS BY ASPIRATION AS WELL AS CNS DEPRESSION.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%

WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:EYES: NOT AN IRRITANT. SKIN: IRRITATION, DERMATITIS. INHALATION: ABNORMAL HEART RHYTHMS, RESPIRATORY ARREST, CENTRAL NERVOUS SYSTEM TOXICITY. INGESTION: CENTRAL NERVOUS SYSTEM DEPRESSION.

Medical Cond Aggravated by Exposure:NONE WHEN USED AS INTENDED WITH PLOTTER/ PRINTERS ENGINEERING SYSTEMS PRODUCTS.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH

H LARGE AMOUNTS OF WATER. IF SYMPTOMS DEVELOP, GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. OBSERVE FOR DIFFICULTY IN BREATHING.GET MEDICAL ATTENTION AS NEEDED. INGESTION: DILUTE STOMACH WITH SEVERAL GLASSES OF WATER.DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method

:TCC
Flash Point:102F,39C
Lower Limits:0.5
Upper Limits:7.0
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG.
Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR
ENCLOSED AREAS. COOL EXPOSED CONTAINERS WITH WATER SPRAY. AVOID
BREATHING VAPORS OR FUMES.
Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. RECOVER FREE LIQUID
USING AN ABSORBENT MATERIAL (VERMICULITE, FIRE RETARDENT SAWDUST,
ETC.).
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVOID HANDLING
NEAR HEAT, STRONG LIGHT, SPARKS, OPEN FLAMES, STRONG OXIDANTS.
Other Precautions:AVOID BREATHING VAPORS. AVOID PROLONGED OR REPEATED
SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHEN USED AS INTENDED WITH
PLOTTER/ PRINTERS ENGINEERING SYSTEMS PRODUCTS.
Ventilation:NONE REQUIRED WHEN USED AS INTENDED WITH PLOTTER/PRINTERS
ENGINEERING SYSTEMS PRODUCTS.
Protective Gloves:NITRILE/NEOPRENE FOR PROLONGED CONTACT.
Eye Protection:NONE NORMALLY REQUIRED.
Other Protective Equipment:NONE REQUIRED WHEN USED AS INTENDED WITH
PLOTTER/PRINTERS ENGINEERING SYSTEMS PRODUCTS.
Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:320F,160C
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN
Decomp Temp:Decomp Text:NOT GIVEN
Vapor Pres:1
Vapor Density:5.0
Spec Gravity:0.77
Evaporation Rate & Reference:0.3 (N-BUTYLACETATE=1)
Solubility in Water:IMMISCIBLE
Appearance and Odor:BLACK LIQUID. SLIGHT ODOR.
Per

cent Volatiles by Volume:100%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM OR CALCIUM HYPOCHLORITE.

Stability Condition to Avoid:HIGH HEAT,SOURCES OF IGNITION.

Hazardous Decomposition Products:FUMES, SMOKE, CARBON MONOXIDE IN THE CASE OF INCOMPLETE COMBUSTION.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE TONER MAY BE CLASSIFIED AS AN IGNITABLE HAZARDOUS WASTE (D001) AND SHOULD BE DISPOSED AT AN APPROVED DISPOSAL SITE OR FACILITY IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.