

SHERWIN WILLIAMS CO -- B69B40 PART A, COAL TAR EPOXY COATINGS (SUPDA)

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 01-310-7675  
MSDS Date: 01/01/1991  
MSDS Num: BSGHJ  
Product ID: B69B40 PART A, COAL TAR EPOXY COATINGS (SUPDAT)  
MFN: 01  
Kit Part: Y  
Responsible Party  
Cage: 54626  
Name: SHERWIN WILLIAMS CO  
Address: 101 PROSPECT AVE  
City: CLEVELAND OH 44115  
Info Phone Number: 216-566-2902  
Emergency Phone Number: 216-566-2917  
Proprietary Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 54626  
Name: SHERWIN WILLIAMS COMPANY  
Address: 101 PROSPECT AVE NW  
City: CLEVELAND OH 44115  
Phone: 216-566-2902  
Cage: 54636  
Name: SHERWIN-WILLIAMS CO THE  
Address: 101 PROSPECT AVE NW  
City: CLEVELAND OH 44115-1042  
Phone: 800-251-2486/216-566-2242

=====  
Item Description Information  
=====

Item Name: EPOXY COATING KIT  
=====

Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----  
=====

Health Hazards Data  
=====

===

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: ACUTE:IRRIT OF EYES, SKIN & RESP SYS. MAY CAUSE NERVOUS SYS DEPRESS. EXTREME OVEREXP MAY RSLT IN UNCON & POSS DEATH. HDCH, DIZZ, NAUS & LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOS TO VAP/S PRAY MISTS. REDNESS & ITCHING/BURNING SENSATION MAY INDICATE EYE/EXCESSIVE SKIN EXPOS. CH

RONIC:HUMAN & (EFTS OF OVEREXP)

Signs And Symptions Of Overexposure: HLTH EFTS:ANIMAL STUDIES INDICATE PRLNG OVEREXP TO COAL TAR PITCH CAN CAUSE CANCER OF SKIN, LUNG, BLADDER & GI TRACT. INHAL OF COAL TAR PITCH VOLAT @ APPLICATN TEMP WOULD NOT BE EXPECTED AS THEY ARE V APORIZED ONLY @ VERY HIGH TEMP. PRLNG OVEREXP TO SOLV INGRED IN PROD MAY CAUSE ADVERSE EFTS TO LIVER, URINARY &

Medical Cond Aggravated By Exposure: MAY CAUSE ALLERGIC SKIN REACTION IN SUSCEPTIBLE PERSONS.

F

irst Aid: INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. EYES: FLUSH WITH LAR GE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: GET MEDICAL ATTENTION.

=====

Handling and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: WASTE MAY BE HAZ AS DEFINED UNDER RCRA 40 CFR261. MUST BE TESTED FOR IGNIT TO DETERM APPLIC EPA HAZ WASTE NUMBERS. INCIN IN APPRVD FACILITY. DO NOT INCIN CLSD CNTNR. DISPOSE OF IN ACCORDANCE WITH FED, STATE & LOCAL REGULATIONS REGARDING POLLUTION.

Handling And Storage Precautions: KEEP AWAY FROM HEAT & OPEN FLAME. DURING USE & UNTI

L ALL VAP GONE:KEEP AREA VENT. DO NOT SMOKE. EXTING ALL FLAMES,  
PILOT LIGHTS & HEATERS.

Other Precautions: THIS PROD MUST BE MIXED W/OTHER COMPONENTS BEFORE USE.  
BEFORE OPENING PACKAGES, READ & FOLLOW WARNING LABELS ON ALL COMPONENTS.  
INTENTIONAL MISUSE BY DELIB CONC & INHALING CONTENTS CAN BE HARMFUL/FATA  
L. COATING MAY CONTAIN MATLS

=====  
Fire and Explosion Hazard Information  
=====

=====  
Flash Point Text: 106F,41C

Lower Limits: 0.7%

Upper Limits: 7%

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP(FP  
N). WATER SPRAY MAY BE INEFTIVE. IF WATER USED, FOG NOZZ PREF. WATER MAY BE  
USED TO COOL CLSD CNTNRS TO (SUPDAT)

Unusual Fire/Explosion Hazard: KEEP CNTNR TIGHTLY CLSD. ISOLATE FROM HEAT, ELEC  
EQUIP, SPK & OPEN FLAME. CLSD CNTNRS MAY EXPLODE WHEN EXPOS TO EXTREME  
HEAT. APPLICATIO  
N TO HOT SURF (SUPDAT)

=====  
Control Measures  
=====

Respiratory Protection: FOR SPRAY APPLICATN, WEAR NIOSH/MSHA APPRVD FULL FACE  
POS PRESS AIR SUPPLIED RESP, TC19C. FOR BRUSH APPLICATN, WEAR NIOSH/MSHA  
APPRVD ORG VAP RESP. FOLLOW RESP MFR'S DIRECTIONS FOR USE. WHEN SANDING/A  
BRADING DRIED FILM, WEAR DUST/

Ventilation: LOC EXHST PREF. GEN EXHST ACCEPTABLE IF EXPOS MAINTAINED BELOW  
APPLIC

EXPOS LIM. REFER TO OSHA STD 1910.94, 107, 108.

Protective Gloves: NITRILE/NBR GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: USE BARRIER CREAM ON EXPOSED SKIN. FOR SPRAY  
APPLICATION, WEAR FULL BODY DISPOSABLE PROTECTIVE CLOTHING.

Work Hygienic Practices: USE ONLY W/ADEQ VENT. DO NOT BREATHE VAP/SPRAY MIST.  
DO NOT GET IN EYES/ON SKIN/ON CLTHG. WASH HANDS AFTER USING.

Supplemental Safety and Health: USERS OF "L" VERSION SHOULD CONSULT "LR"  
VERS

ION FOR ADDNL INFO(FP N). MFR'S TRADE NAME/PART NO:HI-MIL SHER-TAR. FIRE  
FIGHT PROC:PVNT PRESS BUILD-UP & POSS AUTOIGNIT/EXPLOS WHEN EXPOS TO  
EXTREME HEAT. EXPLO HAZ:REQS SPEC PREC. DURING EMER CNDTNS OVEREXP TO DECOMP  
PROD MAY CAUSE HLTH HAZ. SYMP MAY NOT BE IMMED APPARENT.

=====  
Physical/Chemical Properties  
=====

B.P. Text: >281F,>138C

Vapor Pres: SEE INGS

Vapor Density: HVR/AI

R

Spec Gravity: 1.1-1.2

Evaporation Rate & Reference: SLOWER THAN ETHER

Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume: 0-36

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: NONE KNOWN.

Materials To Avoid: NONE KNOWN.

Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE.

Hazardous Polymerization Indicator

: NO

Conditions To Avoid Polymerization: NOT RELEVANT.

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 54626

Trans ID NO: 124241

Product ID: B69B40 PART A, COAL TAR EPOXY COATINGS (SUPDAT)

MSDS Prepared

Date: 01/01/1991

Review Date: 02/17/1994

MFN: 1

Multiple KIT Number: 0

Kit Part IND: Y

Review IND: Y

Detail DOT Information

DOT PSN Code: GIX

Symbols: G

DOT Proper Shipping Name: FLAMMABLE LIQUIDS, CORROSIVE, N.O.S.

Hazard Class: 3

UN ID Num: UN2924

DOT Packaging Group: I

Label: FLAMMABLE LIQUID, CORROSIVE

Special Provision: T42

Non Bulk Pack: 201

Bulk Pack: 243

Max Qty Pass: 0.5 L

M

ax Qty Cargo: 2.5 L  
Vessel Stow Req: E  
Water/Ship/Other Req: 40

=====  
Detail IMO Information  
=====

IMO PSN Code: HIA  
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. o  
IMDG Page Number: 3345  
UN Number: 1993  
UN Hazard Class: 3.3  
IMO Packaging Group: III  
Subsidiary Risk Label: -  
EMS Number: 3-07  
MED First Aid Guide NUM: T

=====  
Detail IATA Informa  
tion  
=====

IATA PSN CA  
IATA UN ID Num: 1993  
IATA Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. \*  
IATA UN Class: 3  
IATA Label: FLAMMABLE LIQUID  
UN Packing Group: III  
Packing Note Passenger: 309  
Max Quant Pass: 60L  
Max Quant Cargo: 220L  
Packaging Note Cargo: 310

=====  
Detail AFI Information  
=====

AFI PSN Code: XXX  
=====

=====  
HAZCOM Label  
=====

Product ID: B69B40 PART A, COAL TAR EPOXY COATINGS (SUPDAT)  
Cage: 54626  
Company Name: SHERWIN WILLIAMS COMPANY  
Street: 101 PROSPECT AVE NW  
City: CLEVELAND OH  
Zipcode: 44115  
Health Emergency Phone: 216-566-2917  
Label Required IND: Y  
Date Of Label Review: 12/21/1993  
Status Code: C  
Label Date: 12/21/1993  
Origination Code: G  
Chronic Hazard IND: Y  
Eye Protection IND: YES  
Skin Protection IND: YES  
Signal Word:

**WARNING**

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Moderate

Reactivity Hazard: None

Hazard And Precautions: ACUTE: EYES, SKIN & RESP SYS IRRITANT. MAY CAUSE NERVOUS SYS DEPRESS. HEADACHE, DIZZINESS, NAUSEA & INCOORDINATION ARE INDICATIONS OF EXCESSIVE EXPOS TO VAP/SPRAY MISTS. REDNESS & ITCHING/BURNING SENS ATION MAY INDICATE EYE/EXCESSIVE SKIN EXPOS. INTENTIONAL MISUSE MAY BE HARMFUL/FATAL. CHRONIC: PRLNG OVEREXP TO SOLVENTS M

AY CAUSE

ADVERSE EFFECTS TO LIVER, URINARY & REPRODUCTIVE SYSTEMS. REPORTS HAV E ASSOCIATED RPTD/PRLNG OVEREXP TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.