

INLAND TECHNOLOGY INC -- FS000 SKYSOL -- 6850-01-381-4420

===== Product Identification =====

Product ID:FS000 SKYSOL

MSDS Date:10/13/1994

FSC:6850

NIIN:01-381-4420

MSDS Number: BSGMR

=== Responsible Party ===

Company Name:INLAND TECHNOLOGY INC

Address:2612 PACIFIC HWY NO C

City:TACOMA

State:WA

ZIP:98424

Country:US

Info Phone Num:800-552-3100

Emergency Phone Num:800-255-3924

CAGE:0K209

=== Contrac

tor Identification ===

Address:401 E 27TH STREET

Box:City:TACOMA

State:WA

ZIP:98421-1203

Country:US

Phone:800-552-3100/253-383-1177

CAGE:0K209

===== Composition/Information on Ingredients =====

Ingred Name:C12-C13 PARAFFINIC HYDROCARBONS OR MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Other REC Limits:NONE RECOMMENDED

Ingred Name:D-LIMONENE

CAS:5989-27-5

RTECS #:GW6360000

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

===

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: NO HEALTH EFFECTS NOTED FOR  
INHALATION. CONTACT MAY CAUSE EYE IRRITATION. LOW ORDER ORAL AND  
DERMAL TOXICITY. CHRONIC: PROLONGED OR REPEATED SKIN EXPOSURE CAN  
LEAD TO MILD IRRITATION, DEFATTING AND DERMATITIS.  
Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF  
0.  
1% OR GRETAER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.  
Effects of Overexposure:EYES: REDNESS, TEARING, DISCOMFORT. SKIN:  
REDNESS, ITCHING, DISCOMFORT.  
Medical Cond Aggravated by Exposure:SKIN CONTACT MAY AGGAVATE EXISTING  
DERMATITIS.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES OR UNTIL  
IRRITATION SUBSIDES. IF IRRITATION PERSISTS, SEE DOCTOR.  
SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP  
AND WATER.  
INGESTED: DO NOT INDUCE VOMIT ING! GET IMMEDIATE MEDICAL  
ATTENTION.INHALED-REMOVE FROM EXPOSED AREA. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:152F,67C  
Lower Limits:0.6%  
Upper Limits:7%  
Extinguishing Media:FOAM, DRY CHEMICAL, WATER SPRAY OR CARBON DIOXIDE.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
FULL PROTECTIVE GEAR FOR ENCLOSED OR CONFINED SPACES OR AS  
OTHERWISE NEEDED.  
Unusual Fire/Explosion Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF AND ELIMINATE ALL SOURCES OF  
IGNITION. CONTAIN AND COLLECT SPILLED MATERIAL. ABSORB RESIDUE.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE AND STORE AWAY FROM SOURCES OF  
IGNITION, STRONG OXIDIZING AGENTS AND STRONG

ACIDS. KEEP CONTAINER  
SEALED WHEN NOT IN USE.

Other Precautions:MINIMIZE BREATHING VAPOR OR MIST. AVOID PROLONGED OR  
REPEATED CONTACT WITH SKIN. WASH CONTAMINATED CLOTHING BEFORE  
REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE ADEQUATE MECHANICAL DILUTION VENTILATION WHENEVER  
PRODUCT IS USED IN A CONFINED SPACE, HEATED ABOVE ROOM TEMPERATURE

Protective Gloves:NITRILE

Eye Protection:SAFETY

GLASSES/GOGGLES/FACE SHIELD

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,  
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS PRESENTED BY CAGE 0K209 FOR CONTRACT SP0450-96-D-4114.

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:340F,171C

Vapor Pres:5

Spec Gravity:0.77

Evaporation Rate & Reference: