View NSN Online: https://aerobasegroup.kr/nsn/6830-00-965-9647

DUPONT E I DE NEMOURS & CO, INC, POLYMER PRODUCTS -- HALON 1301 FIRE EXTINGUISHANT -- 6830-00-965-9647

Product ID:HALON 1301 FIRE EXTINGUISHANT MSDS Date:10/24/1991 FSC:6830 NIIN:00-965-9647 **MSDS Number: BSHLK** === Responsible Party === Company Name: DUPONT E I DE NEMOURS & CO, INC, POLYMER PRODUCTS Address:1007 N MARKET ST City:WILMINGTON State:DE ZIP:19898 Countr y:US Info Phone Num:800-441-9450 Emergency Phone Num:800-441-3637/CHEMTREC 800-424-9300 Preparer's Name:K.P. BROWN CAGE:9V583 === Contractor Identification === Company Name: CEREBERUS PYROTRONICS (201-267-1300) CAGE:0KDN3 Company Name: DUPONT E I DE NEMOURS AND CO INC, POLYMER PRODUCT-TEFLON CO. Address:1007 MARKET ST Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:800-523-0372/346-4748 CAGE:9V583

Ingred Name:TRIFL UOROBROMOMETHANE (HALON 1301) (SARA III) CAS:75-63-8 RTECS #:PA5425000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9394 Ozone Depleting Chemical:1

LD50 LC50 Mixture:TLV=1000 PPM;6090MG/M3 8HR TWA Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL:13%-MAY CAUSE HEART IRREGULARITIES.

 SKIN/EYE:CONTACT WITH THE LIQUID MAY CAUSE FROSTBITE. Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA. Effects of Overexposure:INHAL:13%-IRREGULAR PULSE,PALPITATIONS,INADEQUATE CIRCULATION. Medical Cond Aggravated by Exposure:PERSONS WITH PREEXISTING DISEASE OF THE CARDIOVASCULAR OR CENTRAL NERVOUS SYSTEMMAY BE AT INCREASED RISK FROM EXPOSURE.
======================================
First Aid:INHAL:IMMEDIATELY REMOVE TO FRESH AIR.KEEP PERSONS CALM.IF NOT BREATHING,GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED.SKIN:FLUSH WITH WATER.TREAT FOR FROSTBITE BY GENTLY WARMING AREA.EYES:IMMEDIATE LY FLUSH WITH WATER.CALL PHYSICIAN.INGEST:NOT A LIKELY ROUTE OF EXPOSURE.
======================================
 Flash Point:WILL NOT BURN Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:U SE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:CYLINDERS MAY RUPTURE.HAZARDOUS DECOMPOSITION PRODUCTS MAY BE RELEASED.
======================================
Spill Release Procedures: USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.REMOVE SOURCES OF IGNITION.VENTILATE AREA, ESP. LOW PLACES.
Neutralizing Agent:NONE
<pre>====================================</pre>
Handling and Storage Precautions:STORE IN ACLEAN DRY AREA WITH TEMPERATURES 1 ETHER=1 Solubility in Water:NEGLIGIBLE (0.03%) Appearance and Odor:LIQUIFIED GAS;COLORLESS;ETHER-LIKE ODOR Percent Volatiles by Volume:100
======================================
Stability Indicator/Materials to Avoid:YES ALKALI,ALKALINE EARTH METALS(EG.POWDERED AL,ZN,BE). Stability Condition to Avoid:EXTENDED CONTACT WITH OPEN FLAMES AND TEMPERAT

URES >1000F. Hazardous Decomposition Products:FREE BROMINE,CARBONYL HALIDES.

Waste Disposal Methods:RECLAIM(BY DISTILLATION) OR USE PERMITTED WASTE DISPOSAL IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, e

xpressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.