

SOUTH COAST TERMINALS INC -- 1126 ULTRALUBE, ENGINE OIL SAE 30 -- 9150-00-186-6681  
===== Product Identification =====

Product ID:1126 ULTRALUBE, ENGINE OIL SAE 30  
MSDS Date:10/27/1993  
FSC:9150  
NIIN:00-186-6681  
MSDS Number: BSKTF  
=== Responsible Party ===  
Company Name:SOUTH COAST TERMINALS INC  
Address:7401 WALLISVILLE RD  
Box:15535  
City:HOUSTON  
State:TX  
ZIP:77020-3555  
Country:US  
Info Phone Num:713-  
672-2401 EXT 232  
Emergency Phone Num:713-672-2401-232/800-424-9300(CHEM  
CAGE:1L506  
=== Contractor Identification ===  
Company Name:SOUTH COAST TERMINALS, INC  
Address:7401 WALLISVILLE ROAD  
Box:15535  
City:HOUSTON  
State:TX  
ZIP:77020  
Country:US  
Phone:713-672-2401/800-424-9300(CHEMTREC)  
CAGE:1L506

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL/BASE OIL/LUBRICATING OIL BASESTOCK  
CAS:8002-05-9  
RTECS #:SE7175000  
Fraction by Wt: 80-90%  
Other REC Limits:NON

E SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ZINC SALT OF DIALKYL DITHIOPHOSPHORIC ACID

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE-THIS MATERIAL MAY CAUSE EYE

IRRITATION. SKIN-THIS MATERIAL MAY CAUSE SKIN IRRITATION.

INHALATION-EXPOSURE TO HEATED

MIST OR VAPORS MAY CAUSE IRRITATION

TO THE NOSE AND THROAT.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:EYE-DIRECT CONTACT MAY CAUSE BURNING, TEARING,

AND REDNESS. SKIN-PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS,

BURNING AND DERMATITIS. INHALATION-EXPOSURE TO HEATED MIST OR VAPOR

MAY CAUSE IRRITATION TO NOSE AND THROAT. INGESTION-ACCIDENTAL

INGESTION MAY CAUSE IRRITATION TO THE DIGESTIVE TRACT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:ORAL-IF INGESTED, DON'T INDUCE VOMITING; CALL A PHYSICIAN

IMMEDIATELY. EYE-FOR DIRECT CONTACT, FLUSH EFFECTED EYES WITH CLEAN

WATER. IF IRRITATION/REDNESS PERSISTS, SEE PHYSICIAN. SKIN-WASH

WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING. INHALATION-IF

IRRITATION DEVELOPS, MOVE AWAY FROM THE SOURCE OF EXPOSURE. IF

IRRITATION PERSISTS, SEE PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point:392F,200C (MIN)

Extinguishing Media:EXTINGUISH WITH DRY CHEMICAL, CARBON DIOXIDE, WATER

SPRAY, FOAM, AND SAND OR EARTH. WATER & FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:RESPIRATORY PROTECTION AND EYE PROTECTION

REQUIRED FOR FIRE FIGHTING PERSONNEL.

Unusual Fire/Explosion Hazard:NONE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:TREAT AS AN OIL SPILL. CONTAIN AND REMOVE BY



===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. ENCLOSED-CONTROLLED INCINERATION IS RECOMMENDED UNLESS DIRECTED OTHERWISE BY APPLICABLE ORDINANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.