

LHB INDUSTRIES -- ECO-SURE BLACK 17038 AEROSOL

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 01-331-6107  
MSDS Date: 12/18/1992  
MSDS Num: BSSMR  
Product ID: ECO-SURE BLACK 17038 AEROSOL  
MFN: 03  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 631  
34  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141  
Preparer's Name: RUDOLF OPPENHEIM  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: ENAMEL  
Specification Number: A-A-2787  
Type/Grade/Class: TYPE 1  
Unit of Issue: PT  
UI Container Qty: 0  
Type of Container: METAL  
=====

Ingredients

=====  
Cas: 1330-20-7  
RTECS #: ZE2100000  
Name: XYLENE (SARA III)  
% Wt: &lt;22.10  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

Cas: 110-12-3  
RTECS #: MP3850000  
Name: METHYL ISOAMYL KETONE  
% Wt: 5.82  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 50 PPM  
ACGIH TLV: 50 PPM  
-----

Cas: 64742-95-6  
RTECS #: SE75465  
00  
Name: AROMATIC 150  
% Wt: &lt;2.91  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 5 PPM  
ACGIH TLV: 5 PPM  
-----

Cas: 64742-95-6  
RTECS #: SE7546500  
Name: AROMATIC 100  
% Wt: 5.82  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 50 PPM  
ACGIH TLV: 50 PPM  
-----

Cas: 108-10-1  
RTECS #: SA9275000  
Name: METHYL ISOBUTYL KETONE (SARA III)  
% Wt: &lt;2.91  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 100 PPM  
ACGIH TLV: 50 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS  
-----

-

-----  
Cas: 107-87-9  
RTECS #: SA7875000  
Name: METHYL PROPYL KETONE  
% Wt: &lt;2.91  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 200 PPM  
ACGIH TLV: 200 PPM  
-----

Cas: 95-63-6  
RTECS #: DC3325000  
Name: 1,2,4-TRIMETHYLBENZENE (SARA III)  
% Wt: &lt;2.91  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 25 PPM  
ACGIH TLV: 25 PPM  
-----

Cas: 71-36-3  
RTECS #: EO1400000  
Name: N-BUTYL ALCOHOL (SARA III)  
% Wt: &lt;2.91  
Other REC Limits: NONE SPECI  
FIED  
OSHA PEL: 50 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS  
-----

Cas: 115-10-6  
RTECS #: PM4780000  
Name: DIMETHYL ETHER  
% Wt: 22.65  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: NOT ESTABLISHED  
-----

RTECS #: 9999999VO  
Name: VOC: 65%  
Other REC Limits: NONE SPECIFIED  
-----

=====  
Health Hazards Data  
=====

R

oute Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATING & INHALING CONTENTS HARMFUL/ FATAL.

REPEATED/PROLONGED OVEREXPOSURE ASSOCIATED WITH PERMANENT BRAIN & NERVOUS

SYSTEM DAMAGE. IN CONFINED AREA, IN HIGH CONCENTRATION ARE ANESTHETIC. SKIN & RESPIRATORY TRACT IRRITATION. LIGHT HEADED, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION

Signs And Symptions Of Ove

rexposure: IRRITATION TO EYES, THROAT, AND

RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH SOAP & WATER; WASH CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES.

CONTACT PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLOWED , DO NOT INDUCE VOMITING. GET IMMEDIATEMEDICAL AID. IF INHALED, REMOVE TO FRESH AIR. GIVE

ARTIFICIAL RESPIRATIO

N IF NECESSARY. GET MEDICAL AID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====  
Handling and Disposal

=====  
Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE IN ACCORD WITH FEDERAL, STATE, LOCAL REGULATIONS. DO NOT PUNCTURE, INCINERATE, OR STORE ABOVE 120F. EXPOSU

RE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN T RASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F. AVOID BREATHING SPRAY, MIST, OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL

MISUSE BY DELIBERATE LY CONCENTRATING AND INHALING OR SWALLOWING CO NTENTS MAY BE HARMFUL OR FATAL.

=====  
Fire and Explosion Hazard Information

=====  
Flash Point Text: NR

Autoignition Temp Text: 662 F

Lower Limits: 3.4

Upper Limits: 18.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIV

E, USE TO COOL FIRE EXPOSED  
CONTAINERS. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL FROM BURSTING,  
RUPTURING, OR VENTING OF CONTAINERS.  
Unusual Fire/Explosion Hazard: DON'T SPRAY NEAR OPEN FLAME. AT ELEVATED  
TEMPERATURES (>120F) CONTAINERS MAY VENT, RUPTURE, OR BURST. AEROSOL  
CONTAINER; DO NOT EXPOSE TO TEMPERATUE ABOVE 120F.

=====  
Control Measures  
=====

Respiratory Protection: NONE  
BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.  
Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT  
POINT OF MIST OR SPRAY RELEASE.  
Protective Gloves: TO PROTECT SKIN  
Eye Protection: CHEMICAL SPLASH GOGGLES  
Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH  
STATIONS.  
Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE  
WHILE USING PRODUCT.

=====  
Physical/Chemical Pro  
perties  
=====

HCC: V3  
Vapor Pres: 63 @ 68F  
Vapor Density: 1.6  
Spec Gravity: 1.063 (WATER=1)  
Solubility in Water: INSOLUBLE  
Appearance and Odor: BLACK / PAINT

=====  
Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: EXTREME HEAT  
Hazardous Decomposition Products: CARBON MONOXIDE  
Hazardous Polymerization Indicator: NO  
=====

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
=====  
Other Information  
=====  
=====

=====  
=====  
Transportation Information  
=====

Responsible Party Cage: 0FTT5  
Trans ID NO: 126039  
Product ID: ECO-SURE BLACK 17038 AEROSOL  
MSDS Prepared Date: 12/18/1992  
Review Date: 05/11/1995  
MFN: 3  
Multiple KIT Number: 0  
Review  
IND: Y  
Unit Of Issue: PT  
Container QTY: 0  
Type Of Container: METAL  
Additional Data: NONE  
=====

=====  
=====  
Detail DOT Information  
=====

DOT PSN Code: AGC  
DOT Proper Shipping Name: AEROSOLS, FLAMMABLE,  
DOT PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
Hazard Class: 2.1  
UN ID Num: UN1950  
Label: FLAMMABLE GAS  
Special Provision: N82  
Non Bulk Pack: NONE  
Bulk Pack: NONE  
Max Qty Pass: 75 KG  
Max Qty Cargo: 150 KG  
Vessel Stow Req: A  
Water/Ship/Other Req: 40,48,85  
=====

=====  
=====  
Detail IMO Information  
=====

IMO PSN Code: AIY  
IMO Proper Shipping Name: AEROSOL DISPENSERS ?  
IMO PSN Modifier: ,WITH A CAPACITY OF 1000 CUBIC CM OR LESS  
IMDG Page Number: 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 2-13  
=====

=====  
=====  
Detail IA  
=====

TA Information

=====  
IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203  
=====

Detail AFI Information

=====  
AFI PSN Code: ALR  
AFI Symbols: \*  
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.  
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)  
AFI Hazard Class: 2.1  
AFI UN ID NUM: UN1950  
Special Provisions: P4  
Back Pack Reference: A6.3  
=====

HAZCOM Label

=====  
Product ID: ECO-SURE BLACK 17038 AEROSOL  
Cage: 0FTT5  
Company Name: LHB INDUSTRIES  
Street: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO  
Zipcode: 63134  
Health  
Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141  
Label Required IND: Y  
Date Of Label Review: 05/11/1995  
Status Code: C  
MFG Label NO: UNKNOWN  
Label Date: 05/11/1995  
Origination Code: G  
Eye Protection IND: YES  
Skin Protection IND: YES  
Signal Word: WARNING  
Health Hazard: Slight  
Contact Hazard: Slight  
Fire Hazard: Moderate  
Reactivity Hazard: None  
Hazard And Precautions: CONCENTRATING & INHALING CONTENTS HARMFUL/ FATAL.  
REPEATED/PROLONGED OVEREXPOSURE ASSOCIATED WITH PERMANENT BRAIN & N

ERVOUS

SYSTEM DAMAGE. IN CONFINED AREA, IN HIGH CONCENTRATION ARE ANESTHETIC. SKIN & RESPIRATORY TRACT IRRITATION. LIGHT HEADED, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES, THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United State

s of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.