

MOBIL OIL CORP -- MOBIL AERO OIL 80 -- 9150-00-412-2065

===== Product Identification =====

Product ID:MOBIL AERO OIL 80

MSDS Date:06/10/1991

FSC:9150

NIIN:00-412-2065

MSDS Number: BSVZ

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-737-4411/CHEMT

REC 800-424-9300

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWES ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

Company Name:SYLLOR INC/EASE CHEMICAL, A JOINT VENTURE

Address:2800 SHIRLINGTON RD, SUITE 704

Box:City:ARLINGTON

State:VA

Z

IP:22206
Country:US
Phone:703-998-0036
CAGE:0HZM8
Company Name:UNI-KEM INTERNATIONAL
Address:1001 HARIMAW COURT EAST
Box:City:METAIRIE
State:LA
ZIP:70001
Country:US
Phone:504-835-7600/FAX:504-835-7608
CAGE:4S446

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL
CAS:64742-65-0
RTECS #:PY8038500
Other REC Limits:NONE RECOMMENDED

Ingred Name:SOLVENT DEWAXED RESIDUAL OIL (PETROLEUM) NOTE: INGREDIENTS
1 & 2 COMBINED ARE GREATER THAN 95% OF THE PRODUCT.
T.
CAS:64742-62-7
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACRYLATE POLYMER
Fraction by Wt: 450F,>232C
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:FOR FIRES IN ENCLOSED AREAS,FIRE FIGHTERS
SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. USE
WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE
Unusual Fire/Explosion Hazard:WATER OR FOAM MAY CAUSE FROTHING.
PREVENT RUNOFF OR
DILUTION FROM ENTERING STREAMS, SEWERS, DRINKING
WATER. USE WATER TO FLUSH SPILLS FROM EXPOSURE.

=====
Accidental Release Measures
=====

Spill Release Procedures:REPORT SPILL AS REQUIRED BY REGULATIONS.
ABSORB ON FIRE RETARDANT SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL
UP AND DISPOSE OF AT APPROPRIATE WASTE FACILITY I/A/W FEDERAL,
STATE & LOCAL REGULATIONS AND PRODUCT CHARACTERISTICS AT TIME OF
DISPOSAL.

=====
Handling and Storage
=====

rage =====

Handling and Storage Precautions:PERSONS WHO REGULARLY HANDLE USED MOTOR OIL SHOULD MINIMIZE CONTACT WITH THE OIL. WASH ANY SKIN CONTACT AREAS AND REMOVE OIL SOAKED CLOTHING.

Other Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Ventilation:USE IN A WELL VENTILATED AREA.

Protecti

ve Gloves:NO SPECIAL EQUIPMENT REQUIRED

Eye Protection:NO SPECIAL EQUIPMENT REQUIRED

Other Protective Equipment:NO INFORMATION GIVEN ON MSDS BY MFR.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICE SHOULD ALWAYS BE FOLLOWED.

Supplemental Safety and Health

THIS PRODUCT IS FROM SEVERELY HYDROTREATED STOCKS AND AS SUCH IS NOT CONSIDERED CARCINOGENIC. HOWEVER *USED* MOTOR OIL FROM GASOLINE ENGINES HAS PRODUCED CANCERS WITH SKIN PAINTING, WHILE OIL USED IN DIESEL ENGINES DOES NOT.

OT.

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: