View NSN Online: https://aerobasegroup.kr/nsn/6750-00-401-9918

Product ID:GRAPH TEK DISPERSANT GT 9020

MSDS Date:11/14/1990

FSC:6750

NIIN:00-401-9918

MSDS Number: BTCJD
=== Responsible Party ===
Company Name:OLIN CORP
Address:120 LONG RIDGE RD

Box:1355

City:STAMFORD

State:CT

ZIP:06904-1355

Country:US

Info Phone Num:203-356-3449

Emergency Phone Num:203-356-3449

CAG E:8X135

=== Contractor Identification ===

Company Name: OLIN CORP

Address:51 CORPORATE WOODS 9393 W 110 ST

City:OVERLAND PARK

State:KS ZIP:66210 Country:US

Phone:800-432-6546

CAGE:8X135

Company Name: OLIN CORPORATION

Address:501 MERRITT 7

Box:4500

City:NORWALK

State:CT


ZIP:06856-4500 Country:US

Phone:203-750-3000/800-511-MSDS

CAGE:99530

====== Composition/Information on Ingredients ========

Ingred Name:ISOPARAFFINIC HYDROCARBONS (NAPHTHA PETROLEUM), HYDROTREATED HEAVY, NON AROM



Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. REMOVE ALL SOURCES OF IGNITION. STOP SOURCES AS SOON AS POSSIBLE. REMOVE W/A VACUUM SYSTEM/PUMPING DEVICE. CREATE DIKE/TRENCH TO CONTAIN/SPIILL MATERIALS MAY BE ABSORB USING CLAY/SAND/NON-FLAMMABLE COM

MERCIAL ABSORBENT. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: IF VAPORS MISTS, OR AEROSOLS ARE GENERATED, WEAR A NIOSH/MSHA APPROVED RESPIRATOR. Ventilation: LOCAL EXHAUST VENTILATION IS RECOMMENDED IF VAPORS, MISTS/AEROSOLS ARE GENERATED. OTHERWISE USE GENERAL EXHAUST. Protective Gloves: IMPERMEABLE GLOVES Eye Protection: CHEMICAL GOGGLES Other Protective Equipment: IMPERVIOUS BOOTS, APRON, PROTECTIVE SUIT Work Hygienic Practices: CLOTHIN G SHOULD BE LAUNDERED BEFORE RE-USE. Supplemental Safety and Health CON'T ON INHALATION: KEEP THE PERSON WARM & AT REST. CALL A PHYSICIAN. IN THE EVENT THAT AN INDIVIDUAL INHALES ENOUGH VAPOR TO LOSE CONSCIOUSNESS, PERSON SHOULD BE MOVED TO FRESH AIR AT ONCE & A PHYSI CIAN SHOULD BE CALLED IMMEDIATELY. IF BREATHING HAS STOPPED, ARTIFICIAL RESPIRATION SHOULD BE GIVEN IMMEDIATELY. ========= Physical/Chemical Properties ===========

Boiling Pt:B.P. Text:313-380F

V

apor Pres: