

BOW SOLDER PRODUCTS CO. -- SOLDER, TIN ALLOY -- 3439-01-007-5491
===== Product Identification =====

Product ID:SOLDER, TIN ALLOY
MSDS Date:09/01/1986
FSC:3439
NIIN:01-007-5491
MSDS Number: BTCMS
=== Responsible Party ===
Company Name:BOW SOLDER PRODUCTS CO.
Address:900 HOBSON STREET
Box:488
City:UNION
State:NJ
ZIP:07083
Country:US
Info Phone Num:(201) 686-6040
Emergency Phone Num:(201) 686-6040
Pr
eparer's Name:DGSC-SSH
CAGE:52329
=== Contractor Identification ===
Company Name:BOW ELECTRONIC SOLDERS
Address:1 CROSSMAN ROAD
Box:City:SAYREVILLE
State:NJ
ZIP:08872
Country:US
Phone:732-316-2100/ FAX: 732-316-2177
CAGE:52329

===== Composition/Information on Ingredients =====

Ingred Name:TIN
CAS:7440-31-5
RTECS #:XP7320000
Fraction by Wt: 63.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9394

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF75250

00

Fraction by Wt: 35.53%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE 1910.1025
ACGIH TLV:0.15 MG/M3,DUST;9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)
CAS:7440-36-0
RTECS #:CC4025000
Fraction by Wt: 0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG (SB)/M3; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:BISMUTH
CAS:7440-69-9
RTECS #:EB2600000
Fraction by Wt: 0.25%
Other REC Limits:NONE SPECIFIED

Ingred Name:COPPER (SARA III)
CAS:
7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0.08%
Other REC Limits:1 MG(CU)/M3 (DUST)
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2 MG/M3 FUME; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ARSENIC (SARA III)
CAS:7440-38-2
RTECS #:CG0525000
Fraction by Wt: 0.03%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE 1910.1018
ACGIH TLV:0.01 MG/M3, A1; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 0.02%
Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3
ACGIH TLV:10 MG/M3 AS FE2O3

Ingred Name:ALUMINUM (SARA III)
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: 0.005%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15MG/M3 DUST/5 FUME
ACGIH TLV:10MG/M3 DUST; 9394

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 0.005%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ROSIN ACID
CAS:8050-09-7
Other REC Limits:NONE SPECIFIED

Ingred Name:CADMIUM (SARA III)
CAS:7440-43-9
RTECS #:EU9800000
Fraction by Wt: 0.08%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 MG/M3 DUST; Z-2
ACGIH TLV:0.01 MG/M3 DUST;9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

==== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: BURNS. INGESTION: LEAD POISONING
& METALLIC TASTE IN MOUTH. INHALATION:

ABDOMINAL PAIN, NAUSEA,
JOINT OR MUSCLE PAIN, WEAKNESS, LOSS OF WEIGHT, MENTAL CONFUSION, &
LEAD-LINE ON GUMS.

Explanation of Carcinogenicity:LEAD & ARSENIC ARE SUSPECTED HUMAN
CARCINOGENS.

Effects of Overexposure:SKIN: BURNS. INGESTION: LEAD POISONING &
METALLIC TASTE IN MOUTH. INHALATION: ABDOMINAL PAIN, NAUSEA, JOINT
OR MUSCLE PAIN, WEAKNESS, LOSS OF WEIGHT, MENTAL CONFUSION, OR
LEAD-LINE ON GUMS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

==

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: DON'T ATTEMPT TO
REMOVE ROSIN FROM SECOND OR THIRD DEGREE BURNS. USE SOLVENTS TO
REMOVE ROSIN FROM MINOR FIRST DEGREE BURNS. INGESTION: OBTAIN
MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:>300F,>149C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:NONFLAMMABLE. USE MEDIA SUITABLE F
OR SURROUNDING
FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED RESPIRATORY SYSTEM.

Unusual Fire/Explosion Hazard:MODERATE HAZARD WHEN HIGH CONCENTRATION
OF VERY FINE METALLIC DUST IS EXPOSED TO HEAT. MOLTEN METAL MAY
REACT VIOLENTLY WITH WATER.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM OR WET SWEEP USING A RESPIRATOR &
PROTECTIVE CLOTHING.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Hand
ling and Storage =====

Handling and Storage Precautions:STORE IN A CLOSED CONTAINER. AVOID
INHALATION OF DUSTS OR FUMES. DON'T SMOKE OR EXPOSE FOOD TO DUST.
KEEP AREA CLEAN.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION
EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER
CURRENT 29 CFR 1910.134, INSTRUCTION

S/WARNINGS AND NIOSH RESPIRATOR
SELECTION.

Ventilation:LOCAL EXHAUST: FUME HOOD OVER AREA. MECHANICAL: 200 FT/MIN.
AIR VELOCITY INTO HOOD OPENING TO KEEP 1700F,>927

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:0.000016

Vapor Density:NOT GIVEN

Spec Gravity:7.3-11.3

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:INSOLUBLE

Appearance and Odor:METALLIC COLOR, SOLID, GRAY TO SHINY SILVERY GRAY.

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACIDS, BASES, OXIDIZERS, & WATER

Stability Condition to Avoid:EXTREME TEMPERATURES

Hazardous Decomposition Products:TOXIC FUMES

===== Disposal Considerations =====

Waste Disposal Methods:SCRAP DRIPPINGS & DROSSES SHOULD BE STORED IN A
CLOSED CONTAINER & RETURNED TO A LEAD RECYCLER. FOLLOW FEDERAL,
STATE, & LOCAL REGULATIONS REGARDING DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.