

PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV -- COATING, ALIPH POLYMUR BROWN 383, 30051, ID 705220 -- 8010-01-233-0060

=====
Product Identification
=====

Product ID:COATING, ALIPH POLYMUR BROWN 383, 30051, ID 705220

MSDS Date:12/27/1993

FSC:8010

NIIN:01-233-0060

MSDS Number: BTCNX

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:K

S

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ISOBUTYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE
16 MM HG @ 20C) (LFL 1.0; UFL 8.0)

CAS:108-10-1

RTECS

#:SA9275000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM; STEL 75 PPM

ACGIH TLV:50 PPM; STEL 75 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE (SOLVENT) (SARA III) (VAPOR PRESSURE 10
MM HG @ 20C) (LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SARA III) (VAPOR

PRESSURE 5 MM HG @ 20C) (LFL 1.0;
UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:50 PPM; 147 MG/M3

EPA Rpt Qty:1000 LBS

DOT R

pt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - QUARTZ (PIGMENT)

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: