

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- COATING, POLYURETHANE, BROWN
383, 30051 P/N 754209 -- 8010-01-160-6746

=====
Product Identification
=====

Product ID:COATING, POLYURETHANE, BROWN 383, 30051 P/N 754209

MSDS Date:05/11/1993

FSC:8010

NIIN:01-160-6746

Kit Part:Y

MSDS Number: BTGHT

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WI

CHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE (SOLVENT) (VAPOR
PRESSURE 2 MM HG @ 20C)

CAS:108-65-6

RTECS #:A

I8925000

Fraction by Wt: 15%

Other REC Limits:NONE RECOMME

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)
(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMME

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE 70
MM HG @ 20C) (LFL 2.0; UFL 10.0)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 15%

Ot

her REC Limits:NONE RECOMME

OSHA PEL:200 PPM;STEL 300 PPM

ACGIH TLV:200 PPM;STEL 300 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1) (SKIN)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMME

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:50 PPM; 147 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - QUARTZ (PIGMENT)

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: