View NSN Online: https://aerobasegroup.kr/nsn/6810-00-822-7637 CROWN CHEMICAL CORP -- ISOPROPYL ALCOHOL 99% ANHYDROUS -- 6810-00-822-7637 Product ID:ISOPROPYL ALCOHOL 99% ANHYDROUS MSDS Date:01/04/1990 FSC:6810 NIIN:00-822-7637 MSDS Number: BTHVK === Responsible Party === Company Name: CROWN CHEMICAL CORP Address:1888 NIRVANA AVE City: CHULA VISTA State:CA ZIP:92011-6118 Country:US Info Phone Num:619-421-6601 **Emergency Phone N** um:619-421-6601 **CAGE:1194X** === Contractor Identification === Company Name: CROWN CHEMICAL CORP Address:1888 NIRVANA AVE Box:City:CHULA VISTA State:CA ZIP:92011-6118 Country:US **CAGE:1194X** ======= Composition/Information on Ingredients ======== Ingred Name: ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL;9394

============= Hazards Identification ========================

LD50 LC50 Mixture:

ORAL LD50 (RAT) = 5840 MG/KG

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE-LIQUID IS IRRITATING TO EYES.

SKIN-LIQUID IS MILDLY IRRITATING TO THE SKIN. INHALATION-VAPORS MAY BE IRRITATING TO THE NOSE, THROAT & RESPIRATORY TRACT. HIGH VAPOR CONCENTRATIONS MAY CAUSE CNS DEP RESSION. INGESTION-EARLY TO MODERATE CNSDEPRESSION.

Explanation of Carcinogenicity:THIS CHEMICAL IS NOT LISTED AS HAVING

ANY EVIDENCE OF BEING CARCINOGENIC.

Effects of Overexposure:EYE-MAY CAUSE PAIN, TEARING, AND INFLAMMATION. SKIN-SKIN IRRITATION & DERMATITIS. INGESTION-GIDDINESS, HEADACHE, NAUSEA AND DIZZINESS; IN EXTREME CASES UNCONSCIOUSNESS AND DEATH MAY OCCUR. ASPIRATION PNEUMONITIS MAY EVIDENCED BY COUGHING, LABORED BREATHING AND CYANOSIS, IN SEVERE CASES DEATH.

Medical Cond Aggravated by Exposure:PREEXISTING EYE, AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=======================================	First Aid Measures	=======================================
---	--------------------	---

First Aid:EYE-HOLD EYELIDS OPEN & FLUSH WITH PLENTY OF WATER FOR 15 MIN. GET MEDICAL ATTENTION. SKIN-REMOVE CLOTHIN/SHOES. FLUSH SKIN WITH WATER. THEN WASH WITH SOAP/WATER. IF IRRITATION OCCURS, CONTACT PHYSICI AN. INHALATION-REMOVE VICTIM TO FRESH AIR, IF BREATHING IS HARD, PROVIDE OXYGEN; IF NOT BREATHING GIVE CPR. GET MEDICAL ATTENTION. INGESTION-DO NOT INDCUE VOMITING. GET MEDICAL ATT

ENTION.

=======================================	Fire Fighting Measures	
---	------------------------	--

Flash Point:=11.7C, 53.F

Lower Limits:2
Upper Limits:12

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. DO NOT USE DIRECT WATER STREAM. PRODUCT WILL FLOAT & REIGNITE.

Fire Fighting Procedures:WEAR FULL BUNKER GEAR, INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CONTAINERS EXPOSED TO I

COULD RESULT IN CONTAINER RUPTURE.
========= Accidental Release Measures ===========
Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINER. SEAL TIGHTLY AND IDENTIFY FOR PROPER DIS POSAL. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:STOW CONTAINERS IN A SAFE NON-TRAFFIC AREA. KEEP CONTAINER TIGHTLY CLOSED & WELL IDENTIFIED. Other Precautions:DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE A NIOSH APPROVED RESPIRATOR O AVOID OVER EXPOSURE, WHEN ANTICIPATED EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS. USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURYFYING RESPIRATOR FOR ORGANIC VAPORS. Ventilation:USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS. Protective Gloves:WEAR CHEMICAL RESISTANT GLOVES. Eye Protection:WEAR SAFETY GLASSES OR GOGGLES. Other Protective Equipment:WERA CHEMICAL RESIATNT CLOTHES AS REQUIRED. Work Hygienic Practices:AIR DRY CONTAMINATED CLOTHING IN A WELL VENTI LATED AREA. LAUNDER BEFORE REUSE. Supplemental Safety and Health AVOID PROLONGED OR REPEATED CONTACT WITH THE SKIN.
HCC:F2 Boiling Pt:=82.2C, 180.F Melt/Freeze Pt:

FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR BUILDUP WHICH

NTENSE HEAT FROM