

DEFT, INC -- CAT, MIL-C-85285B, 26231, P/C 04GY008CAT -- 8010-01-293-3017

===== Product Identification =====

Product ID:CAT, MIL-C-85285B, 26231, P/C 04GY008CAT

MSDS Date:03/16/1992

FSC:8010

NIIN:01-293-3017

Kit Part:Y

MSDS Number: BTJPP

=== Responsible Party ===

Company Name:DEFT, INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-474-0400

Emergency Phon

e Num:800-424-9300 CHEMTREC

Preparer's Name:MIKE SMITH

CAGE:5M511

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

Company Name:DEFT, INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Phone:714-474-0400

CAGE:5M511

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC ISOCYANATE (VAPOR PRESSURE 0 MM HG)

CAS:28182-81-2

R

TECS #:NQ9170000
Fraction by Wt: 75%
Other REC Limits:NONE SPECIFIED

Ingred Name:HEXAMETHYLENE DIISOCYANATE (HDI) FREE MONOMER CONTENT LESS THAN 0.5% (TIME OF MFR), AFTER 3-6 MO, MAY RISE TO 1.6% MAX.

CAS:822-06-0
RTECS #:MO1740000
Fraction by Wt: 0.5-1.6%
Other REC Limits:MOBAY: 0.02 PPM CEIL
ACGIH TLV:0.005 PPM TWA
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:METHYL ISOBUTYL KETONE (SARA III) (VAPOR PRESSURE 15 MM HG @ 68F)

CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 14.45%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM; STEL 75 PPM
ACGIH TLV:50 PPM; STEL 75 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL 3-ETHOXYPROPIONATE (VAPOR PRESSURE 0.7 MM HG @ 68F)

CAS:763-69-9
RTECS #:UF3325000
Fraction by Wt: 10%
Other REC Limits:50 PPM; STEL 100 PPM

Ingred Name:VOC: 260 G/L

RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Repo

Health Hazards Acute and Chronic:INHAL:RESP TRACT IRRIT (HEADACHE,DIZZY,STAGGER,CONFUSION,UNCONSCIOUS,COMA). SKIN: ISOCYANATES REACT W/SKIN PROTEIN & MOISTURE.IRRIT (SWELL,RED,RASH).ABSORPTN:IRRIT (DRY,DEFAT,SKIN CRACK). EYES:IRRIT (TEAR,RED,SWELL W/STING). INGEST:IRRIT, CORROSIVE IN GI TRACT.VOMITING MAY CAUSE ASPIRATION,RESULTING IN CHEM PNEUMONITIS

Effects of Overexposure:ACUTE: VAPORS ARE IRRITATING TO EYES, NOSE, & TH

ROAT. INHALATION MAY CAUSE HEADACHES, DIFFICULT BREATHING & UNCONSCIOUSNESS. CHRONIC: AS RESULT OF PREVIOUS REPEATED OVEREXPOSURE OR SINGLE LARGE DOSE, CERTAIN INDIVIDUALS WILL DEVELOP ISOCYANATE SENSITIZATION (REACT TO LATER EXPOSURE OF ISOCYANATE LEVELS BELOW TLV).

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE SENSITIZATION.

=====
===== First Aid Measures =====
=====

First Aid:INHAL:MOVE TO FRESH AIR.RESTORE BREATHING.ASTHMATIC TYPE SYMPTOMS MAY DEVELOP (IMMEDIATE/DELAYED BY SEVERAL HRS).GET MEDICAL AID. SKIN:REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREAS W/SOAP & WATER.W ASH CONTAMINATED CLOTHING BEFORE REUSE.EYES:FLUSH W/LUKEWARM WATER (LOW PRESSURE) 15 MIN,LIFT EYELIDS.GET MED AID. INGEST:DON'T INDUCE VOMITING.DON'T GIVE ANYTHING TO UNCONSCIOUS PERSON.GET MED AID.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TCC

Flash Point:60.0F,15.6C

Lower Limits:1.05

Upper Limits:8.00

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, WATER SPRAY

Fire Fighting Procedures:USE FULL PROTECT CLOTH/FIREFIGHT EQUIP W/SCBA. WATER MAY BE USED TO COOL CLSD CNTNRS (PREVENT PRESS BLDUP/AUTOIGNIT/EXPLOS). HDI/IRRIT VAPOR GENERATED BY FIRE.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD. KEEP FROM HEAT/IGNIT SOURCE. CLSD CNTNR MAY EXPLODE W/HEAT. APPLIC TO HOT

SURFACE REQ

SPECIAL PRECAUTION. OVEREXPOSURE TO DECOMP PROD-HLTH HZD.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA. CONTAIN & REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BLDG IN COMPLY W/OSHA

1910.106,IN TIGHT CLOSD CNTNR IN VENTD AREA.AVOID STORING NEAR HIGH TEMP/IGNIT SOURCE.PREVENT PROLONGED VAPOR BREATHING

Other Precautions:KEEP CONTAINERS TIGHT & UPRIGHT (PREVENT LEAK). PROLONGED OVEREXPOSURE MAY CAUSE ALLERGIC REACTION. AVOID CONTACT WITH SKIN & EYES. DO NOT INGEST. DO NOT HANDLE TILL MFR'S PRECAUTIONS READ OR UNDERSTOOD. SMOKE IN SMOKING AREAS ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR RECOMMENDED FOR USE IN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING/AIR SUPPLIED).OBEY OSHA REGS FOR RESPIRATOR. VENT TO PROVIDE TO KEEP EXPOSURE LEVELS BELOW OSHA LIMITS. VAPOR PARTIC RESPIRATOR (TC23C) WHERE BELOW 10 TIMES TLV/PEL.

Ventilation:EXHAUST VENT TO KEEP AIRBORNE CONCENTRATION OF SOLVENT, HDI & POLYISOCYANATES BELOW TLV. REMOVE IGNITION SOURCES.

Protective Gloves:COTTON, NEOPRENE, RUBBER, POLYETHYLENE

Eye Protection:FACE/SIDE SHLD,SPLASH GUARD,CHEM GOGGLES

Other Protect

ive Equipment:THE USE OF LONG SLEEVE AND LONG LEG CLOTHING

IS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:241 TO 338F

Vapor Density:> AIR

Spec Gravity:1.03962

Evaporation Rate & Reference:0.83 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER

LIQUID WITH SOLVENT ODOR
Percent Volatiles by Volume:30.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid:CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE W/FEDERAL, STATE, & LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED W/CARE, DUE TO PRODUCT RESIDUE & FLAMMABLE VAPOR. DO NOT INCINERATE CLOSED CONTAINERS. EPA HZD CODE:D001,F003,F005.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.