

OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP -- 212-19 / OMEGA 1024 -- 6850-00-559-2836

=====
Product Identification
=====

Product ID:212-19 / OMEGA 1024

MSDS Date:11/01/1991

FSC:6850

NIIN:00-559-2836

MSDS Number: BTKQY

=== Responsible Party ===

Company Name:OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP

Address:6935 WEST 62ND STREET

City:CHICAGO

State:IL

ZIP:60638

Country:US

Info Phone Num:312-586-8000

Emergency Phone Num:312-586-8000, 800-424-9300

Preparer's Name:PAUL ZALANTIS

CAGE:0B5U9

=== Contractor Identification ===

Company Name:OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP

Address:6935 WEST 62ND STREET

City:CHICAGO

State:IL

ZIP:60638

Country:US

Phone:312-586-8000, 800-424-9300

CAGE:0B5U9

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES,STREIGHT RUN MIDDLE

CAS:64741-44-2

RTECS #:LX3296000

Fraction by Wt: 88%

Other REC Limits:NONE RECOMMENDED

=

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: HIGH CONCENTRATIONS IRRITATING TO EYES AND RESPIRATORY TRACT. HEADACHES, DIZZINESS, NAUSEA. CHRONIC: MAY CAUSE LOSS OF CONSCIOUSNESS, BURNING TO EYES, SKIN IRRITATION. INGESTION MAY BE FATAL.
Effects of Overexposure:IRRITATION TO SKIN OR EYES, REDNESS.
Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
First Aid Measures
=====

First Aid:WASH AREAS OF CONTACT WITH GENEROUS AMOUNTS OF WARM WATER AND MILD SOAP. FOR EYES, FLUSH THOROUGHLY WITH WATER AND SEEK MEDICAL ATTENTION IMMEDIATELY. IF INHALED, REMOVE FROM EXPOSURE AND SEEK MEDICAL ATTENTION IF NECESSARY. IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:135F,57C
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:TREAT AS HYDROCARBON FIRE.
Unusual Fire/Explosion Hazard:NONE.

=====
Accidental Release Measures
=====

Spill Release Procedures:IF OUTDOORS, ADD SAND, ERATH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING. INSIDE SPILLAGE, ELIMINATE ALL IGNITION SOURCES AND REMOVE WITH ABSORBENT MATERIAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:REASONABLE CARE AND PRECAUTIONS WHEN HANDLING THIS MATERIAL ARE STRONGLY RECOMMENDED.
Other Precautions:REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:CARTRIDGE TYPE FOR SOLVENT.
Ventilation:MECHANICAL, GENERAL, SHOULD BE SUFFICIENT TO REDUCE LEVELS BELOW TLV.
Protective

Gloves:NEOPRENE GLOVES.

Eye Protection:FACE SHIELD AND/OR GOGGLES.

Other Protective Equipment:APRON AND/OR SPLASH GAURD.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

HAZARD CLASS: FLAMMABLE.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:250F,121C

Melt/Freeze Pt:M.P/F.P Text:-20F,-29C

Vapor Density: