View NSN Online: https://aerobasegroup.com/nsn/6850-00-965-2331

Product ID:212-19 / OMEGA 1024 MSDS Date:11/01/1991 FSC:6850 NIIN:00-965-2331 MSDS Number: BTKSJ === Responsible Party === Company Name: OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP Address:6935 WEST 62ND STREET City:CHICAGO State:IL ZIP:60638 Country:US Info Phone Num:312-586-800 0 Emergency Phone Num:312-586-8000, 800-424-9300 Preparer's Name: PAUL ZALANTIS CAGE:0B5U9 === Contractor Identification === Company Name: OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP Address:6935 WEST 62ND STREET City:CHICAGO State:IL ZIP:60638 Country:US Phone:312-586-8000, 800-424-9300 CAGE:0B5U9 Ingred Name: DISTILLATES, STREIGHT RUN MIDDLE CAS:64741-44-2 RTECS #:LX3296000

Fraction by Wt: 88%

Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: HIGH CONCENTRATIONS IRRITATING TO EYES AND RESPIRATORY TRACT. HEADACHES, DIZZINESS, NAUSEA. CHRONIC: MAY CAUSE LOSS OF CONSCIOUSNESS, BURNING TO EYES, SKIN IRRITATION. INGESTION MAY BE FATAL.
Effects of Overexposure:IRRITATION TO SKIN OR EYES, REDNESS.
Medical Cond Aggra vated by Exposure:NONE KNOWN.

First Aid:WASH AREAS OF CONTSCT WITH GENEROUS AMOUNTS OF WARM WATER AND MILD SOAP. FOR EYES, FLUSH THOROUGHLY WITH WATER AND SEEK MEDICAL ATTENTION IMMEDIATELY. IF INHALED, REMOVE FROM EXPOSURE AND SEEK MEDICAL ATTENTION IF NECESSARY. IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

Flash Po int Method:TCC Flash Point:135F,57C Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL. Fire Fighting Procedures:TREAT AS HYDROCARBON FIRE. Unusual Fire/Explosion Hazard:NONE.

Spill Release Procedures: IF OUTDOORS, ADD SAND, ERATH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING. INSIDE SPILLAGE, ELIMINATE ALL IGNITION SOURCES AND REMOVE WITH ABSORB ENT MATERIAL.

 Handling and Storage Precautions: REASONABLE CARE AND PRECAUTIONS WHEN HANDLING THIS MATERIAL ARE STRONGLY RECOMMENDED.
 Other Precautions: REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:CARTRIDGE TYPE FOR SOLVENT. Ventilation:MECHANICAL, GENERAL, SHOULD BE SUFFICIENT TO REDUCE LEVELS BELOW TLV. Protectiv e Gloves:NEOPRENE GLOVES. Eye Protection:FACE SHIELD AND/OR GOGGLES. Other Protective Equipment:APRON AND/OR SPLASH GAURD. Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health HAZARD CLASS: FLAMMABLE.

HCC:F4 Boiling Pt:B.P. Text:250F,121C Melt/Freeze Pt:M.P/F.P Text:-20F,-29C Vapor Density: