

TRIANGLE COATINGS INC -- TTP25EO10 24300 GR EXTERIOR WOOD PRIMER ALKYD PRIMER --
8010-00-055-5181

===== Product Identification =====

Product ID:TTP25EO10 24300 GR EXTERIOR WOOD PRIMER ALKYD PRIMER

MSDS Date:10/07/1991

FSC:8010

NIIN:00-055-5181

MSDS Number: BTPJR

=== Responsible Party ===

Company Name:TRIANGLE COATINGS INC

Address:1930 FAIRWAY DR

City:SAN LEANDRO

State:CA

ZIP:94577-5631

Country:US

Info Phone Num:415-895-8000

Emergency Phone Num:415-895-8000

CAGE:0GB20

=== Contractor Identification ===

Company Name:TRIANGLE COATINGS INC

Address:1930 FAIRWAY DR

Box:City:SAN LEANDRO

State:CA

ZIP:94577-5631

Country:US

Phone:800-895-8000

CAGE:0GB20

===== Composition/Information on Ingredients =====

Ingred Name:SYNTHETIC RESIN

Fraction by Wt: 15%

Ingred Name:AROMATIC PETROLEUM DISTILLATE, HEAVY STRAIGHT RUN NAPHTHA C

-C12 BOILING PT 149-446F *93-4*

CAS:64741-41-9

Fra

ction by Wt: 25%

Ingred Name:VOL ORGANIC CMPD: 2.73 LB/GAL
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:OVEREXPOSURE CAN LEAD TO CNS
DEPRESSION. EYES: SLIGHT IRRITATION. SKIN: PROLONGED & REPEATED
LIQUID CONTACT CAN CAUSE IRRITATION & DERMATITIS. OVEREXPOSURE MAY
CAUSE BLOOD DISORDERS & NEUROLOGICAL
DIS ORDERS. REPEATED &
PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE PERMANENT BRAIN &
NERVOUS SYSTEM DAMAGE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, LOSS OF
CONSCIOUSNESS, IRRITATION, DEFATTING, DRYING

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER.
INHALATION: REMOVE TO FRESH AIR. PROVIDE OXYGEN, CPR IF NOT
BREATHING. INGESTION: DON'T
INDUCE VOMITING/GIVE ANYTHING BY MOUTH
TO AN UNCONSC IOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:105F
Lower Limits:1
Upper Limits:6
Extinguishing Media:WATER FOG, CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:EVACUATE AREA. WEAR PROTECTIVE CLOTHING, NIOSH
APPROVED SCBA. COOL FIRE-EXPOSED CONTAINERS W/WATER. AVOID
SPREADING BURNING LIQUID W/WATER USED FOR COOLING.
Unus
ual Fire/Explosion Hazard:MATERIAL MAY BE IGNITED BY HEAT, SPARKS,
FLAME, STATIC ELECTRICITY. AUTOIGNITION TEMPERATURE: 445F.

=====
Accidental Release Measures
=====

Spill Release Procedures:STAY UPWIND AWAY FROM MATERIAL. KEEP ALL
SOURCES OF IGNITION & HOT METAL SURFACES AWAY FROM SPILL. INDOOR:
VENTILATE AREA. LARGE: CALL SPILL RESPONSE TEAM. NOTIFY APPROPRIATE
AGENCIES.

=====
Handling and Storage
=====

Handling

and Storage Precautions:AVOID IGNITION SOURCES & STORING W/STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED. STORE IN A COOL DRY PLACE W/ADEQUATE EXPOSION-PROOF VENTILATION.

Other Precautions:IF POURING/TRANSFERRING, CONTAINERS MUST BE BONDED & GROUNDED TO PREVENT ACCUMULATION OF STATIC CHARGE. DON'T WELD/HEAT/DRILL ON/NEAR CONTAINER. EVEN EMPTY CONTAINERS CAN CONTAIN EXPOSIVE VAPORS. INTENTIONAL MISUSE OF PRODUCT: HARMFUL/FATAL.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:DEPENDING ON NATURE & CONCENTRATION OF AIRBORNE MATERIAL USE A RESPIRATOR/GAS MASK W/APPROPRIATE NIOSH APPROVED CARTRIDGES & CANNISTERS/SUPPLIED AIR EQUIPMENT.

Ventilation:EXPLOSION-PROOF AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS. ADDITIONAL VENTILATION/EXHAUST SYSTEMS MAY BE REQUIRED.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED

Work Hygienic Practices:

REMOVE/LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:315-395F

Decomp Temp:Decomp Text:500F

Vapor Density:>1

pH:6-7.5

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT GREEN LIQUID W/MILD AROMATIC SOLVENT

Percent Volatiles by Volume:41.4

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials

to Avoid:YES

ALKALIES, AQUEOUS ACIDS, AMINES, ACIDIC ALCOHOLS, STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, STATIC ELECTRICITY

Hazardous Decomposition Products:CO, CO2

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the

Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.