

YAMANASHI ELECTRIC CO LTD -- OKILASER DRUM KIT, 56106601 -- 6850-01-354-4503

=====
Product Identification
=====

Product ID:OKILASER DRUM KIT, 56106601

MSDS Date:03/11/1988

FSC:6850

NIIN:01-354-4503

MSDS Number: BTRBT

=== Responsible Party ===

Company Name:YAMANASHI ELECTRIC CO LTD

Address:462 OSATO-CHO KOFU-SHT

City:YAMANSHI, JAPAN

Info Phone Num:0552-41-2221

Emergency Phone Num:0552-41-2221

CAGE:

NO487

=== Contractor Identification ===

Company Name:YAMANASHI AVIONICS (ELECTRIC) CO LTD

Address:568 MIYAZAWA KOHSAI-CHOME NAKAKOMA-GUN

Box:City:YAMANASHI

Country:JA

Phone:0552-41-2221

CAGE:S5712

Company Name:YAMANASHI ELECTRIC CO LTD

Address:462 OSATO-CHO KOFU-SHT

Box:City:YAMANSHI, JAPAN

Phone:0552-41-2221

CAGE:NO487

=====
Composition/Information on Ingredients
=====

Ingred Name:BINDER RESIN

CAS:25134-45-6

Fraction by Wt: 0.5%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:CHAR

GE CARRIER TRANSPORT MATERIAL

CAS:103079-11-4

Fraction by Wt: 0.4%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:PIGMENT

CAS:26201-32-1

Fraction by Wt: 0.1%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 99.0%

OSHA PEL:15MG/M3 DUST;5 FUME

ACGIH TLV:10 MG/M3 DUST

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Rep

Routes of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:THE COATED COMPOUNDS OF OPC DRUM (SY-B001) EMERGED SATISFACTORILY FROM THE ACUTE TOXICITY TEST, DOSAGE RANGE, 100-400 MG/KG. AND THEY ARE NOT MUTAGENIC.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15

MINUTES . SKIN:FLUSH WITH COPIOUS AMOUNTS OF WATER . INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTIFICIAL RESPIRATION) . INGEST:CALL MD IMMEDIATELY

=====
===== Fire Fighting Measures =====

Extinguishing Media:WATER, FOAM, CO*2, AND DRY CHEMICALS.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . AVOID INHALATION OF SMOKE.

Unusual Fire/Explosion Hazard:THIS MATERIAL HAS NO UNUSUAL FI

RE AND
EXPLOSION HAZARDS.

===== Accidental Release Measures =====

Spill Release Procedures:IF BROKEN UP INTO PIECES AND SPILLED, SWEEP UP
OR VACUUM.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR

EXPOSURE OF CONCERN .

Ventilation:NOT NECESSARY

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEM WORK GLASSES .

Other Protective Equipment:NONE

Work Hygienic Practices:NOT NECESSARY

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Spec Gravity:1.2 (H₂O=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:GREENISH-BLUE, SOLID CYLINDER AND ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND
LOCAL ENVIRONMENTAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no ma

nner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.